


Thermoplastic Conduit Bushings



- Use to Protect Conductors in Rigid or IMC Conduit from Abrasion/Damage during Pull
- Rounded surface of bushing prevents damage to wire insulation
- Thermoplastic material-heat, impact & torque resistant

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
21732	1/2"	1.06	0.43	100	1,000
21733	3/4"	1.31	0.43	100	1,000
21734	1"	1.59	0.48	50	500
21735	1-1/4"	1.96	0.56	25	250
21736	1-1/2"	2.18	0.56	25	250
21737	2"	2.68	0.59	20	200
21738	2-1/2"	3.25	0.72	-	50
21739	3"	3.87	0.75	-	25
21740	3-1/2"	4.37	0.77	-	25
21741	4"	5.00	0.77	-	10
21742	5"	6.25	1.00	-	10
21743	6"	7.50	1.00	-	10




Malleable Reducing Bushings

- Reduce the trade size of a tapered entry on a conduit fitting
- Threaded for rigid and IMC condulets, Hex Shoulder
- Rolled edge protects wire insulation

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
14700	2-1/2" X 1"	2.83	1.22	-	10
14701	2-1/2" X 1-1/4"	2.83	1.58	-	10
14702	2-1/2" X 1-1/2"	2.83	1.83	-	10
14703	2-1/2" X 2"	2.83	2.28	-	10
14704	3-1/2" X 1-1/2"	3.45	1.83	-	10
14705	3-1/2" X 2"	3.45	2.28	-	10
14706	3-1/2" X 2-1/2"	3.96	2.70	-	10
14707	3-1/2" X 3"	3.96	3.35	-	10
14708	4" X 2-1/2"	4.45	2.70	-	10
14709	4" X 3-1/2"	4.45	4.10	-	10



Steel Reducing Bushings

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
14660	1/2" X 3/8"	.63	.91	100	1,000
14661	3/4" X 1/2"	.85	1.02	100	1,000
14662	1" X 1/2"	.72	1.27	50	500
14663	1" X 3/4"	.72	1.27	50	500
14664	1-1/4" X 1/2"	.82	1.62	10	100
14665	1-1/4" X 3/4"	.82	1.62	25	250
14666	1-1/4" X 1"	.81	1.62	25	250
14667	1-1/2" X 1/2"	.85	1.85	25	100
14668	1-1/2" X 3/4"	.85	1.85	25	100
14669	1-1/2" X 1"	.85	1.85	25	100
14670	1-1/2" X 1-1/4"	.85	1.85	25	250
14671	2" X 1/2"	.97	2.23	10	40
14672	2" X 3/4"	.97	2.23	10	40
14673	2" X 1"	.97	2.23	10	40
14674	2" X 1-1/4"	.97	2.23	10	100
14675	2" X 1-1/2"	.97	2.23	10	100
14676	3" X 1/2"	1.57	3.43	-	10
14677	3" X 3/4"	1.57	3.43	-	10
14678	3" X 1"	1.57	3.43	-	10
14679	3" X 1-1/4"	1.57	3.43	-	10
14680	3" X 1-1/2"	1.57	3.43	-	10
14681	3" X 2"	1.57	3.43	-	10
14682	3" X 2-1/2"	1.57	3.43	-	5
14683	4" X 1/2"	1.68	4.43	-	5
14684	4" X 3/4"	1.68	4.43	-	5
14685	4" X 1"	1.68	4.43	-	5
14686	4" X 1-1/4"	1.68	4.43	-	5
14687	4" X 1-1/2"	1.68	4.43	-	5
14688	4" X 2"	1.68	4.43	-	5
14689	4" X 3"	1.68	4.43	-	5

- Reduce trade size of tapered entry on a conduit fitting
- Threaded for Rigid Conduit & IMC
- Rolled edge protects wire insulation

