




EMT To Box Offset Set Screw Connector - Zinc Die Cast



- Use to connect EMT conduit to a Metal Box or Enclosure where Offset is Required
- Zinc Die-Cast
- Combo Head Set-Screw
- Assembled with Zinc Die Cast Locknut
- Concrete Tight (When Taped)

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
15010	1/2"	2.11	.37	20	200
15011	3/4"	2.85	.75	10	100
15012	1"	3.14	1.19	-	100




EMT To Box Offset Compression Connector - Zinc Die Cast

- Use to connect EMT conduit to a Metal Outlet Box or Enclosure where an Offset is Required
- Zinc Die-Cast
- Compression Style
- Assembled with Zinc Die Cast Locknut
- Concrete Tight (When Taped)

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
15014	1/2"	2.11	.37	20	200
15015	3/4"	2.88	.75	10	100




EMT to EMT Inside Corner Set Screw Pulling Elbows

- Use to Connect EMT Conduit together on a 90° Inside Corner
- Combo Head Set Screws
- Zinc Die Cast

DIMENSIONS = INCHES


CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15020	1/2"	2.32	2.32	.59	10	100
15021	3/4"	2.64	2.64	.78	5	50
15022	1"	2.94	2.94	1.19	-	50



EMT Insulating Bushings

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		BAG QTY
		A	B	
21700	1/2"	.522	.570	100
21701	3/4"	.538	.764	50
21702	1"	.614	.954	25
21703	1-1/4"	.620	1.26	25
21704	1-1/2"	.620	1.44	25
21705	2"	.620	1.86	20
21706	2-1/2"	1.12	2.34	-
21707	3"	1.19	2.78	-
21708	3-1/2"	1.22	3.27	-
21709	4"	1.22	3.71	-



- EMT Insulating Bushings protect cables from abrasion
- Fast & Easy press-on installation
- Meets NEC Article 300-15C requirements
- Listed for use in environmental air handling spaces per 2005 NEC code requirements 300-22C
- Polyethylene rated at 194°F(90°C)