




Liquid Tight Connectors - Straight - Insulated Throat - Malleable Iron




- Terminate and Seal Liquid-tight Flexible Metal Core Conduit to either Oil-tight, Liquid-tight or Rain-tight Box or Enclosure
- Connectors can be used with Tapered Threaded Female Entry or Unthreaded KD using the Sealing Washer and Locknut



DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15161	1/2"	0.91	0.55	1.30	25	250
15162	3/4"	0.98	0.59	1.50	10	100
15163	1"	1.14	0.63	1.81	5	50
15164	1-1/4"	1.22	0.67	2.20	5	50
15165	1-1/2"	1.30	0.43	2.44	10	50
15166	2"	1.50	0.73	2.95	5	25

Liquid Tight Connectors - 90° - Insulated Throat - Malleable Iron





- Terminate and Seal Liquid-tight Flexible Metal Core Conduit to either Oil-tight, Liquid-tight or Rain-tight Box or Enclosure
- Connector can be used with Tapered Threaded Female Entry or Unthreaded KD using the Sealing Washer and Locknut



DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS				INNER BOX	OUTER BOX
		A	B	C	D		
15181	1/2"	1.42	0.55	1.30	1.76	10	100
15182	3/4"	1.73	0.59	1.50	2.01	10	100
15183	1"	2.01	0.65	1.81	2.13	5	50
15184	1-1/4"	2.30	0.67	2.20	2.32	-	10
15185	1-1/2"	2.62	0.71	2.44	2.60	-	10
15186	2"	2.99	0.73	2.95	3.03	-	5

Liquid Tight Connectors - 45° - Insulated Throat - Malleable Iron




- Terminate and Seal Liquid-tight Flexible Metal Core Conduit to either Oil-tight, Liquid-tight or Rain-tight Box or Enclosure
- Connectors can be used with Tapered Threaded Female Entry or Unthreaded KD using the Sealing Washer and Locknut



DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS				INNER BOX	OUTER BOX
		A	B	C	D		
15221	1/2"	1.89	0.55	1.30	1.34	10	100
15222	3/4"	1.97	0.59	1.50	1.57	10	100
15223	1"	2.60	0.65	1.81	1.81	5	50
15224	1-1/4"	2.76	0.67	2.20	2.09	-	10
15225	1-1/2"	3.11	0.71	2.44	2.36	-	10
15226	2"	3.66	0.73	2.95	2.64	-	5

Liquid Tight Connectors - Straight - Insulated Throat - Steel



- Terminate and Seal Liquid-tight Flexible Metal Core Conduit to either Oil-tight, Liquid-tight or Rain-tight Box or Enclosure
- Connectors can be used with Tapered Threaded Female Entry or Unthreaded Knockout using the Sealing Washer and Locknut provided



DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15201	1/2"	0.91	0.47	1.12	25	250
15202	3/4"	1.02	0.53	1.37	10	100
15203	1"	1.12	0.65	1.70	5	50
15204	1-1/4"	1.26	0.67	2.07	5	50
15205	1-1/2"	1.46	0.69	2.30	10	50
15206	2"	1.50	0.73	2.80	5	25

Liquid Tight

NEW