



Liquid Tight Connectors



- For use with metallic and non metallic liquid tight conduit, Type B
- Provides smooth connection
- No sharp edges to damage wire.
- Wire easily pulled through
- U. L. Listed. C.U.L. Listed.

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
NON-METALLIC			
T750-NMLT50	1/2" NON-METALLIC STRAIGHT CONNECTOR	EA	1
T750-NMLT75	3/4" NON-METALLIC STRAIGHT CONNECTOR	EA	1
T750-NMLT9050	1/2" NON-METALLIC 90 DEGREE ELBOW CONNECTOR	EA	1
T750-NMLT9075	3/4" NON-METALLIC 90 DEGREE ELBOW CONNECTOR	EA	1



T750-NMLT50



T750-NMLT9050



Single Piece Liquid Tight Fittings

- Conduit threads onto ferrule and up inside the outer body
- Inside taper squeezes down on conduit for superior liquid tight seal
- Cut portion of conduit does not show, giving a more finished appearance
- Easy to use at a lower cost than regular liquid tight fittings
- U.L. and C.U.L. Listed

DIMENSIONS = INCHES

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T750-SLTC50	1/2" STRAIGHT SCREW-ON FITTING	EA	1
T750-SLTC9050	1/2" 90° SCREW-ON FITTING	EA	1
T750-SLTC75	3/4" STRAIGHT SCREW-ON FITTING	EA	1
T750-SLTC9075	3/4" 90° SCREW-ON FITTING	EA	1



T750-SLTC50



T750-SLTC9050




Non-Metallic Liquid Tight Connectors - Straight

- Terminate and Seal Non-Metallic Liquid-tight Conduit
- Nylon Construction with Zinc Die-Cast Locknut
- UV Resistant

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
21813	1/2"	1.18	0.55	1.42	25	150
21814	3/4"	1.20	0.64	1.69	10	100
21815	1"	1.23	0.72	2.02	5	50
21816	1-1/4"	2.44	0.76	2.40	5	50
21817	1-1/2"	2.70	0.80	2.67	4	40
21818	2"	2.99	0.85	3.28	2	20



Non-Metallic Liquid Tight Connectors - 90°

- 90° Orientation
- Terminate and Seal Non-Metallic liquid-tight Conduit
- Nylon Construction with Zinc Die-Cast Locknut
- UV Resistant

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
21823	1/2"	2.84	0.50	2.03	25	150
21824	3/4"	3.25	0.50	2.33	10	100
21825	1"	3.54	0.60	2.95	5	50
21826	1-1/4"	4.75	0.76	5.20	3	30
21827	1-1/2"	4.75	0.80	5.20	2	20
21828	2"	5.42	0.86	5.80	1	10

