




3/8" NM Connector - Zinc Die Cast




- Used to connect Non-Metallic Sheath Cable and Flexible Cord from .30" to .45" in diameter to Outlet Boxes, Enclosures, or Raceway Systems
- 3/8" size fits 1/2" knockout
- Assembled with Zinc Die Cast Locknut and Combo Screws

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
I5330	3/8"	0.78	0.35	100	1,000

Non-Watertight NM Round Connectors - Zinc Die Cast



- Used with Locknut to Terminate Service Entrance Cable to Enclosure
- Assembled with Zinc Die Cast Locknut and Combo Screws
- For Type SEU and NM Cable

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS				INNER BOX	OUTER BOX
		A	B	C	D		
I5331	3/4"	.83	.32	.83	1.67	40	400
I5332	1"	1.14	.55	1.04	1.95	20	200
I5333	1-1/4"	1.24	.57	1.38	2.20	15	150
I5334	1-1/2"	1.40	.57	1.61	2.60	10	100
I5335	2"	1.50	.65	2.05	3.03	8	80

Non-Watertight NM Oval Connectors - Zinc Die Cast




- Used with Locknut to Terminate NM Cable to Enclosure
- Assembled with Zinc Die Cast Locknut and Combo Screws
- For NM Oval Cable

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
I5337	1-1/4"	2.26	1.29	1.91	10	100
I5338	1-1/2"	2.84	1.30	2.19	10	100
I5339	2"	3.48	1.51	2.76	5	50

Tilt-in NM Connectors - Steel



- To terminate one or more Non-Metallic Sheathed Cables to a Knockout in a dry location box or enclosure
- Zinc Plated Steel
- No locknut Required

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
		A	B		
I9012	1/2"	1.31	.59	100	1000
I9013	3/4"	1.73	.75	-	100
I9014	1-1/4"	1.97	.69	-	50
I9015	1-1/2"	2.52	.78	25	250