


Water-Tight Service Entrance Connectors - Zinc Die-Cast



- Compression Type SEU Connector
- Used to Connect Service Entrance Cable to a Service Enclosure in Wet Locations
- Accepts 2 Insulated Conductors, 1 Bare
- U/Flat Style Conductor Only
- Assembled with Rubber Grommet and Steel Washer
- Locknut Included

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	CABLE SIZE	MAX GROMMET OPENING		OVERALL DIMENSIONS		INNER BOX	OUTER BOX
			LENGTH	WIDTH	A	B		
I5370	1"	#8	.67	.40	1.67	1.45	20	100
I5371	1"	#6	.77	.50	1.67	1.45	20	100
I5372	1"	#4	.81	.53	1.67	1.45	20	100
I5373	1-1/4"	#3	.92	.56	2.05	1.80	10	50
I5374	1-1/4"	#2	.98	.59	2.05	1.80	10	50
I5375	1-1/4"	#1	1.09	.65	2.05	1.80	10	50
I5377	1-1/2"	#2/0	1.34	.86	2.31	2.02	10	50
I5379	2"	#2/0	1.34	.86	2.82	2.39	5	25
I5380	2"	#3/0	1.37	.87	2.82	2.39	5	25
I5381	2"	#4/0	1.50	.90	2.82	2.39	5	25
I5382	2"	#4/0	1.73	1.11	2.82	2.39	5	25



Service Entrance




Underground Feed UF To Box Connector - Zinc Die Cast

- Used to Connect Underground Feeder Cables (UF) To Weatherproof Enclosures in Wet Locations.
- Assembled with a Rubber Grommet and Steel Washer
- Sealing Locknut System

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	CABLE SIZE	MAX GROMMET OPENING		OVERALL DIMENSIONS		INNER BOX	OUTER BOX
			LENGTH	WIDTH	A	B		
I5386	1/2"	14/2, 12/2, 10/2	.475	.235	1.22	1.14	25	250
I5387	3/4"	14/3, 12/3, 10/3, 8/2	.720	.260	1.34	1.20	25	250



- UL 467 listed connector for use with Equipment Ground Conductors, Ground Electrode Conductors and Bonding Jumpers
- The Kenny Clamp bonds the enclosure of a service panelboard, load center, separately derived system or switchboard to the grounding electrode conductor per the requirements of NEC 250.8; 312.5(A); 250.53 D(2); 250.52 (A)(1); 250.52(A)(3); 250.66; 250.104 (D)(1); 250.24; 450.10(A)
- Assures good metallic connection and low impedance path for grounding and bonding of electrical equipment
- 12,000 Amp listed and tested
- Brass

CAT. NO.	MODEL NO.	TRADE SIZE	DIMENSIONS		INNER BOX	OUTER BOX
			A	B		
I5390	KC8ST	8 AWG STRANDED	1.75	1.06	10	100
I5391	KC8SO	8 AWG SOLID	1.75	1.06	10	100
I5392	KC6SO	6 AWG SOLID	1.75	1.06	10	100
I5393	KC6ST	6 AWG STRANDED	1.75	1.06	10	100
I5394	KC4SO	4 AWG SOLID	1.75	1.06	10	100
I5395	KC4ST	4 AWG STRANDED	1.75	1.06	10	100
I5396	KC2ST	2 AWG STRANDED	1.75	1.06	10	100
I5397	KCIAST	1/0 STRANDED	1.75	1.06	10	100
I5398	KC2AST	2/0 STRANDED	1.75	1.06	10	100
I5399	KC3AST	3/0 STRANDED	1.75	1.06	10	100

Kenny Clamps

