



Malleable Mast Support Clamp




- Used to secure Service Entrance Conduit to the Outside surface of a building
- Hinged on one side and bolted on other side for easy installation
- Machined Lag Bolt
- Malleable Iron

DIMENSIONS = INCHES

CAT. NO.	CONDUIT SIZE	DIMENSIONS		BOX QTY
		A	B	
21830	2"	2.48"	0.41"	25
21831	2-1/2"	3.08"	0.44"	25

Conduit Support Split Ring




- Used to secure Service Entrance Conduit to the Outside surface of a building
- Bolted on both sides
- Malleable Iron

DIMENSIONS = INCHES

CAT. NO.	CONDUIT SIZE	BOLT SIZE	DIMENSIONS		BOX QTY
			A	B	
21835	2"	1/2" X 10"	2.70"	0.99"	25
21836	2-1/2"	1/2" X 10"	3.33"	1.07"	25
21837	3"	5/8" X 13"	4.50"	1.04"	10
21838	3-1/2"	5/8" X 13"	5.13"	1.08"	10
21839	4"	5/8" X 13"	5.60"	1.08"	10

Conduit Support Universal




- Used to secure Service Entrance Conduit to the Outside surface of a building
- 1/2" x 10" Bolt
- Zinc Plated Steel

DIMENSIONS = INCHES

CAT. NO.	CONDUIT SIZE	DIMENSIONS		BOX QTY
		A	B	
21833	1-1/4" TO 3"	3.80"	10.00"	20

Malleable U-Bolt Pipe Clamps



- Recommended for supporting or guiding heavy loads along runs of non-insulated pipe
- 2 hex nuts
- Malleable Iron - Galvanized

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS				INNER BOX	OUTER BOX
		A	B	C	D		
21840	1/2"	1.00"	1.25"	2.50"	1.81"	25	250
21841	3/4"	1.12"	1.38"	2.81"	1.81"	25	250
21842	1"	1.38"	1.63"	3.06"	1.81"	25	250
21843	1-1/4"	1.75"	2.00"	3.19"	1.81"	20	200
21844	1-1/2"	2.00"	2.38"	3.50"	1.81"	20	200
21845	2"	2.50"	2.50"	4.50"	2.63"	10	100
21846	2-1/2"	3.00"	3.25"	4.88"	2.63"	-	20
21847	3"	3.63"	3.88"	5.38"	2.63"	-	20
21848	3-1/2"	4.06"	4.56"	5.88"	2.63"	-	20
21849	4"	4.69"	5.06"	6.69"	2.63"	-	20