

- Impact resistant, non-corrosive
- Complete with corrosion resistant, hardened steel nails for securing cable to wood, cement, plaster, brick, etc.
- Nail heads are recessed for minimum exposure
- Smooth saddle prevents damage to insulation
- High-grade injection-molded polyethylene
- Resists rot, rust and the effects of temperature extremes



FIG 1



FIG 2



FIG 3

DIMENSIONS = INCHES

CAT. NO.	FIG	USED FOR WIRE SIZES	COLOR	W X HT X INSIDE HT	INNER BAG	MASTER BAG
35000	1	2 NAIL 12/2 & 14/2 NM & UF (1/2" WIDE)	WHITE	.49 X .31 X .21	100	1,000
35001	1	2 NAIL 10/2 NM & UF (3/4" WIDE)	WHITE	.74 X .31 X .21	100	1,000
35002	2	12/2 & 14/2 NM & UF	WHITE	.39 X .39 X .26	100	1,000
35004	3	14/3 NM	GRAY	.31 X .51 X .32	100	1,000
35006	3	10/3 & 12/3 NM	GRAY	.43 X .65 X .48	100	1,000
35008	3	RG 59 COAX CABLE, CAT 5 UTP 4 PAIR	GRAY	.24 X .35 X .26	100	1,000
35040	3	RG 59 COAX CABLE, CAT 5 UTP 4 PAIR	WHITE	.24 X .35 X .26	100	1,000
35041	3	RG 59 COAX CABLE, CAT 5 UTP 4 PAIR	BLACK	.24 X .35 X .26	100	1,000
35010	3	RG 6 COAX CABLE	GRAY	.28 X .43 X .30	100	1,000
35042	3	RG 6 COAX CABLE	WHITE	.28 X .43 X .30	100	1,000
35043	3	RG 6 COAX CABLE	BLACK	.28 X .43 X .30	100	1,000
35012	3	4 CONDUCTOR TELEPHONE WIRE	GRAY	.14 X .23 X .15	100	1,000
35044	3	4 CONDUCTOR TELEPHONE WIRE	WHITE	.14 X .23 X .15	100	1,000
35045	3	4 CONDUCTOR TELEPHONE WIRE	BLACK	.14 X .23 X .15	100	1,000
35014	2	SMALL CORDS SUCH AS LAMP, THERMOSTAT, SPEAKER & PHONE	WHITE	.24 X .25 X .15	100	1,000



- Plastic insulated staples quickly and easily secure vertical stacks of non-metallic cable
- Electro-zinc plated nails provide strength and durability
- Smooth saddles prevent damage to insulation
- UV-protected Polyethylene saddle resists rot, rust and deterioration
- 1/2" wide, white color

CAT. NO.	CABLE SIZE	INNER BAG	OUTER BAG
35016	(2) 14/2 & 12/2	50	500
35018	(3) 14/2 & 12/2	50	500
35020	(4) 14/2 & 12/2	50	500

Plastic Stacking Staples



Plastic Service Entrance Cable Straps

- Plastic insulated straps quickly and easily secure service entrance cable
- Electro-zinc plated nails provide strength and durability
- Stabilized against UV rays and extreme cold; withstand deterioration and breakage
- Smooth saddles prevent damage to insulation
- Polyethylene Material

CAT. NO.	CABLE SIZE	INNER BAG	OUTER BAG
35022	#6 & #8 SEU	50	500
35024	#2 SEU	25	250
35026	4/0 SEU	25	250
35028	#6 SER & 1/2" EMT	50	500
35030	#2 SER & 3/4" EMT	25	250
35032	2/0 SER	25	250
35034	4/0 SER	25	250



35028 THRU 35034



35022 THRU 35026