

# BATH FANS - RETROFIT KITS



## Included In Kit:

- Inline Fan FG4, 1 pc
- Mounting Bracket, 1 pc
- VT 20M Main Control, 1 pc
- 3" to 4" Adapters, 2 pcs
- Wire Connectors, 2 pcs
- Cable Restaint, 1 pc
- 8' Flexible Insulated 4" Duct, 1 pc
- 12' 14-2 Insulated Electrical Wire, 1 pc
- Operation and Installation Manual, 1 pc



CAT. NO.	DESCRIPTION	CFM	CASE QTY
BFRK 100	4" BATH FAN RETROFIT KIT	135	1



FIG. 1



FIG. 2



FIG. 3

## WALL EXHAUST FAN

### RVF SERIES

- Exterior wall-mount exhaust fan
- Lightweight, compact and easy to install
- The housing can be removed for immediate access to the motor & wiring connections
- Galvanized sheet metal housing with white powder coat
- cULus & cCSAus Listed

### PBW SERIES

- 110 cfm
- Exterior remote mount installation ensures quiet operation
- Unobtrusive grille makes for better aesthetics
- PBW 110H Includes a 50W dimmable halogen bulb
- cULus & cCSAus Listed

CAT. NO.	FIG.	DESCRIPTION	CFM	VOLTAGE	CASE QTY
<b>RVF SERIES</b>					
RVF 4	1	4" EXTERIOR WALL EXHAUST FAN	135	120	1
RVF 6	1	6" EXTERIOR WALL EXHAUST FAN	242	120	1
<b>PBW SERIES</b>					
PBW 110	2	BATH FAN EXT. MOUNT VENT ONLY CEILING GRILL, 4" DUCT	110	120	1
PBW 110H	3	BATH FAN EXT. MOUNT W/ DIM 50W HALO LIGHT, 4" DUCT	110	120	1

## ACCESSORIES



FIG. 1



FIG. 2



FIG. 3



FIG. 4



FIG. 5



FIG. 6



FIG. 7

CAT. NO.	FIG.	DESCRIPTION	CASE QTY
FC 6	1	MOUNTING CLAMPS, 6" DUCT (PAIR)	1
FLD 60	2	LIGHT/FAN SWITCH - UP TO 60 MIN. DELAY 115V	1
IPF 05	3	SPEED CONTROL, 5A, WHITE, DEC PLATE INC.	1
IPHS 5	4	HUMIDITY SENSOR / FAN CONTROL, 120V, 10A	1
FD 60EM	5	ELECTRONIC TIMER, 10/20/30/60 MIN, 20A, 1800W MAX LOAD	1
FAT10	6	ATTIC THERMOSTAT 80-130F, 13A	1
DG 4	7	DESIGNER EXHAUST GRILLE W/ COLLAR, 4" DUCT	1
DG 6	7	DESIGNER EXHAUST GRILLE W/ COLLAR, 6" DUCT	1