


Copper Flex Cable Long Barrel 2 Hole Compression Lugs



- High Conductivity Seamless Copper
- Electro-Tin Plating Resists Corrosion
- Flared/Belled Entry for Easy Insertion of Fine Strand Flexible Cable - Class G, H, I, K(Battery), M(Welding), DLO
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486AB Listed for Applications Thru 35KV

CAT. NO.	WIRE RANGE	STUD SIZE	HOLE SPACE	COLOR CODE	COMM	ASTM CLASS	WELDING CLASS	DLO	DIMENSIONS										BOX QTY
									A	A1	B	C	D	E	F	G	F1	F2	
94702	8	1/4"	5/8"	RED	8	10	10	-	2.19"	0.81"	0.42"	0.08"	0.25"	0.28"	1.26"	0.63"	0.12"	0.32"	50
94703	6	1/4"	5/8"	BLUE	6	8	8	(61)	2.36"	0.98"	0.42"	0.08"	0.25"	0.28"	1.26"	0.63"	0.16"	0.34"	50
94705	6	1/4"	3/4"	BLUE	6	8	8	(61)	2.80"	0.98"	0.42"	0.08"	0.25"	0.28"	1.38"	0.59"	0.16"	0.34"	50
94706	6	3/8"	1"	BLUE	6	8	8	(61)	3.24"	0.98"	0.42"	0.08"	0.41"	0.38"	1.81"	1.00"	0.16"	0.34"	50
94707	6	1/2"	1-3/4"	BLUE	6	8	8	(61)	4.42"	0.98"	0.87"	0.12"	0.51"	0.62"	3.00"	1.75"	0.16"	0.34"	50
94708	4	1/4"	5/8"	GRAY	4	6	6	(105)	2.36"	0.98"	0.49"	0.09"	0.25"	0.28"	1.26"	0.63"	0.16"	0.42"	50
94709	4	1/4"	3/4"	GRAY	4	6	6	(105)	2.88"	0.98"	0.49"	0.09"	0.25"	0.28"	1.38"	0.75"	0.16"	0.42"	50
94710	4	3/8"	1"	GRAY	4	6	6	(105)	3.32"	0.98"	0.42"	0.09"	0.41"	0.38"	1.81"	1.00"	0.16"	0.42"	50
94711	4	1/2"	1-3/4"	GRAY	4	6	6	(105)	4.09"	0.98"	0.87"	0.12"	0.51"	0.62"	2.99"	1.75"	0.16"	0.42"	50
94712	2	1/4"	5/8"	BROWN	2	4	4	(125)	2.52"	1.10"	0.60"	0.10"	0.25"	0.28"	1.26"	0.63"	0.18"	0.49"	25
94713	2	1/4"	3/4"	BROWN	2	4	4	(125)	2.64"	1.10"	0.60"	0.10"	0.25"	0.28"	1.38"	0.75"	0.18"	0.49"	25
94716	2	3/8"	1"	BROWN	2	4	4	(125)	3.46"	1.10"	0.60"	0.10"	0.41"	0.38"	1.81"	1.00"	0.18"	0.49"	25
94717	2	1/2"	1-3/4"	BROWN	2	4	4	(125)	4.25"	1.10"	0.81"	0.10"	0.51"	0.62"	2.99"	1.75"	0.18"	0.49"	25
94718	1	1/4"	5/8"	GREEN	1	2	2	(150)	2.56"	1.10"	0.67"	0.11"	0.25"	0.28"	1.26"	0.63"	0.18"	0.53"	25
94719	1	1/4"	3/4"	GREEN	1	2	2	(150)	3.00"	1.10"	0.67"	0.11"	0.25"	0.28"	1.38"	0.75"	0.18"	0.53"	25
94721	1	3/8"	1"	GREEN	1	2	2	(150)	3.46"	1.10"	0.67"	0.11"	0.41"	0.38"	1.81"	1.00"	0.18"	0.53"	25
94725	1/0	1/2"	1-3/4"	PINK	1/0	1	1	(225)	4.63"	1.20"	0.74"	0.12"	0.51"	0.62"	2.99"	1.75"	0.18"	0.56"	10
94726	2/0	1/4"	3/4"	BLACK	2/0	1/0	1/0	1/0 (275)	2.99"	1.38"	0.81"	0.12"	0.25"	0.28"	1.38"	0.75"	0.24"	0.64"	10
94727	2/0	3/8"	1"	BLACK	2/0	1/0	1/0	1/0 (275)	3.43"	1.38"	0.81"	0.12"	0.41"	0.38"	1.81"	1.00"	0.24"	0.64"	10
94728	2/0	1/2"	1-3/4"	BLACK	2/0	1/0	1/0	1/0 (275)	4.61"	1.38"	0.81"	0.12"	0.51"	0.62"	2.99"	1.75"	0.24"	0.64"	10
94730	3/0	3/8"	1"	ORANGE	3/0	2/0	-	2/0 (325)	3.50"	1.38"	0.90"	0.13"	0.41"	0.38"	1.81"	1.00"	0.24"	0.72"	10
94732	3/0	1/2"	1-3/4"	ORANGE	3/0	2/0	-	2/0 (325)	4.65"	1.38"	0.90"	0.13"	0.51"	0.62"	2.99"	1.75"	0.24"	0.72"	10
94733	4/0	3/8"	1"	PURPLE	4/0	3/0	2/0	3/0 (450)	3.54"	1.42"	1.00"	0.13"	0.41"	0.38"	1.81"	1.00"	0.26"	0.77"	10
94734	4/0	1/2"	1-3/4"	PURPLE	4/0	3/0	2/0	3/0 (450)	4.72"	1.42"	1.00"	0.13"	0.51"	0.62"	2.99"	1.75"	0.26"	0.77"	10
94735	250	3/8"	1"	YELLOW	250	-	3/0	4/0 (550)	3.78	1.61"	1.09"	0.15"	0.41"	0.38"	1.81"	1.00"	0.26"	0.84"	10
94736	250	1/2"	1-3/4"	YELLOW	250	-	3/0	4/0 (550)	4.96	1.61"	1.09"	0.15"	0.51"	0.62"	2.99"	1.75"	0.26"	0.84"	10
94737	300	1/2"	1-3/4"	WHITE	300	4/0	4/0	262.6	5.31	1.97"	1.19"	0.15"	0.51"	0.62"	2.99"	1.75"	0.31"	0.94"	10
94738	350	3/8"	1"	RED	350	250	250	313.1	4.60	1.97"	1.28"	0.17"	0.41"	0.38"	1.81"	1.00"	0.33"	1.02"	10
94739	350	1/2"	1-3/4"	RED	350	250	250	313.1	5.39	1.97"	1.28"	0.17"	0.51"	0.62"	2.99"	1.75"	0.33"	1.02"	10
94740	400	1/2"	1-3/4"	BLUE	400	300	300	350	5.47	1.97"	1.39"	0.18"	0.51"	0.62"	2.99"	1.75"	0.33"	1.08"	10
94741	500	3/8"	1"	BROWN	500	350	350	373.3	5.04	2.24"	1.54"	0.22"	0.41"	0.38"	1.81"	1.00"	0.35"	1.20"	10
94742	500	1/2"	1-3/4"	BROWN	500	350	350	373.3	5.75	2.24"	1.54"	0.22"	0.51"	0.62"	2.99"	1.75"	0.35"	1.20"	10
94744	600	1/2"	1-3/4"	GREEN	600	400	400	444.4	5.79	2.24"	1.72"	0.25"	0.51"	0.62"	2.99"	1.75"	0.39"	1.34"	6
94746	750	1/2"	1-3/4"	BLACK	750	600	500	-	6.30	2.64"	1.90"	0.27"	0.51"	0.62"	2.99"	1.75"	0.43"	1.47"	3

Copper Flex Cable Short Barrel Compression Splices



CAT. NO.	CONDUCTOR RANGE	COLOR CODE	COMM	ASTM CLASS	WELDING CLASS	DLO	DIMENSIONS			BOX QTY
							LENGTH (A)	F1	F2	
94750	8	RED	8	10	10	-	0.90"	0.12"	0.32"	50
94753	2	BROWN	2	4	4	(125)	1.25"	0.18"	0.49"	25
94755	1/0	PINK	1/0	1	1	(225)	1.60"	0.18"	0.56"	10
94756	2/0	BLACK	2/0	1/0	1/0	1/0 (275)	1.75"	0.24"	0.64"	10
94758	4/0	PURPLE	4/0	3/0	2/0	3/0 (450)	1.90"	0.26"	0.77"	10
94759	250	YELLOW	250	-	3/0	4/0 (550)	2.00"	0.26"	0.84"	10
94760	300	WHITE	300	4/0	4/0	262.6	2.10"	0.31"	0.94"	10
94761	350	RED	350	250	250	313.1	2.10"	0.33"	1.02"	10