



Clear Insulated 2 Conductor - Dual Side Entry

- Clear Insulation
- 6061-T6 Aluminum
- Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- Pre-filled with Oxide Inhibitor
- Easy Re-Entry for Changes, Inspection or Troubleshooting
- Plugs Marked with Connector Max Wire Size for Easy ID
- CUGAL Dual Rated for use with Copper and/or Aluminum Wire
- One Wire Per Terminal
- Temperature Range of -49°F to 194°F (-45° to 90°C)
- 600 Volt
- UL 486A/486B Listed
- Indoor Use Only



CAT. NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS			BOX QTY
			LENGTH	WIDTH	HEIGHT	
97312	4 - 14	SLOTTED/HEX	1.13"	1.25"	1.38"	12
97332	2 - 14	SLOTTED/HEX	1.15"	1.50"	1.42"	12
97342	1/0 - 2	3/16	1.69"	1.80"	1.93"	10
97352	2/0 - 6	3/16	1.69"	1.80"	1.93"	10
97392	250 - 6	5/16	2.18"	2.48"	2.37"	6

CAT. NO.	WIRE RANGE	ALLEN HEX	DIMENSIONS			BOX QTY
			LENGTH	WIDTH	HEIGHT	
97412	350 - 6	5/16	2.50"	2.67"	2.50"	6
97432	500 - 6	5/16	2.98"	3.38"	2.85"	4
97532	600 - 250	5/16	2.98"	3.38"	2.85"	4
97631	750 - 250	3/8	3.33"	3.44"	3.52"	2
97632*	750 - 250	3/8	3.33"	3.44"	3.52"	2

* Dual Set Screw Configuration (4 Set Screws - 2 Per Port)



Clear Insulated Dual Side Entry

CAT. NO.	NO. OF PORTS	WIRE RANGE	ALLEN HEX	DIMENSIONS			BOX QTY
				LENGTH	WIDTH	HEIGHT	
97314	3	4 - 14	SLOTTED	1.50"	1.21"	1.45"	6
97316	4			1.92"			6
97320	6			2.75"			4
97322	8			3.59"			3
97333	3	2 - 14	SLOTTED	1.60"	1.21"	1.45"	6
97334	4			2.02"			6
97336	6			2.85"			4
97338	8			3.69"			3
97354	3	2/0 - 14	3/16"	1.90"	1.80"	1.85"	8
97356	4			2.49"			6
97360	6			3.67"			4
97362	8			4.85"			3
97373	3	3/0 - 14	1/4"	2.10"	2.09"	1.99"	6
97374	4			2.87"			6
97376	6			4.41"			3
97378	8			5.96"			3
97394	3	250 - 6	5/16"	2.40"	2.40"	2.49"	6
97396	4			3.29"			4
97400	6			5.06"			3
97402	8			6.83"			3
97414	3	350 - 6	5/16"	2.80"	2.75"	2.64"	6
97416	4			3.85"			4
97420	6			5.95"			3
97422	8			8.06"			3
97434	3	500 - 4	5/16"	3.18"	2.97"	3.03"	4
97436	4			4.35"			4
97440	6			6.70"			2
97442	8			9.05"			2
97539	3	600 - 250	5/16"	3.40"	3.25"	3.11"	4
97540	4			4.68"			4
97541	6			7.23"			2
97542	8			9.78"			2
97425	3	750 - 250	3/8"	3.60"	3.85"	3.60"	4
97426	4			5.03"			4
97427	6			7.88"			4
97428	8			10.73"			2

