



Straight Solid Pin Terminal Connectors

- Straight Solid Pin
- All-Aluminum Pin Terminal designed for Termination of both Aluminum and Copper Conductors - Tin Plated
- Barrel is Pre-Filled with Oxide Inhibitor
- Die Index and Crimp Marks on Barrel
- Supplied with EPDM Insulating Cover
- Rated 600 Volt



CAT. NO.	WIRE SIZE	PIN SIZE	DIMENSIONS						COLOR CODE	INNER BOX	OUTER BOX
			O.D.	I.D.	PIN DIA.	TOTAL LENGTH	PIN LENGTH	BODY LENGTH			
90970	6	4	0.598"	0.220"	0.240"	1.85"	0.681"	1.17"	GRAY	25	250
90971	4	4	0.598"	0.236"	0.240"	1.85"	0.681"	1.17"	GREEN	25	250
90972	2	4	0.598"	0.299"	0.240"	1.84"	0.680"	1.16"	PINK	25	250
90973	1	3	0.598"	0.318"	0.250"	1.99"	0.830"	1.16"	GOLD	10	100
90974	1/0	2	0.598"	0.370"	0.290"	1.99"	0.830"	1.16"	TAN	10	100
90975	2/0	1	0.850"	0.429"	0.330"	2.20"	0.830"	1.37"	OLIVE	10	100
90976	3/0	1/0	0.850"	0.476"	0.370"	2.59"	1.22"	1.37"	RUBY	10	100
90977	4/0	2/0	0.850"	0.476"	0.370"	2.59"	1.22"	1.37"	WHITE	10	100
90978	250 MCM	3/0	1.09"	0.594"	0.460"	2.62"	1.22"	1.40"	RED	10	100
90979	300 MCM	4/0	1.09"	0.653"	0.530"	2.73"	1.33"	1.40"	BLUE	10	100
90980	350 MCM	250	1.09"	0.716"	0.570"	2.73"	1.33"	1.40"	BROWN	10	100
90981	400 MCM	300	1.31"	0.763"	0.620"	3.07"	1.59"	1.48"	GREEN	10	100
90982	500 MCM	350	1.31"	0.826"	0.680"	3.07"	1.59"	1.48"	PINK	10	100
90983	600 MCM	400	1.46"	0.921"	0.720"	3.67"	1.64"	2.03"	YELLOW	3	30
90984	750 MCM	500	1.46"	1.03"	0.810"	3.78"	1.75"	2.03"	YELLOW	3	30

Offset Solid Pin Terminal Connectors

- Offset Solid Pin
- All-Aluminum Pin Terminal Designed for Termination of Both Aluminum and Copper Conductors - Tin Plated
- Barrel is Pre-Filled with Oxide Inhibitor
- Die Index and Crimp Marks on Barrel
- Supplied with EPDM insulating cover
- Rated 600 Volt



CAT. NO.	WIRE SIZE	PIN SIZE	DIMENSIONS					COLOR CODE	INNER BOX	OUTER BOX	
			O.D.	I.D.	PIN DIA.	TOTAL LENGTH	PIN LENGTH				BODY LENGTH
90985	2/0	1	0.850"	0.440"	0.330"	2.69"	1.12"	1.57"	OLIVE	10	100
90986	3/0	1/0	0.850"	0.500"	0.370"	2.80"	1.25"	1.55"	RUBY	10	100
90987	4/0	2/0	0.850"	0.547"	0.420"	2.78"	1.27"	1.51"	WHITE	10	100
90988	250 MCM	3/0	1.09"	0.594"	0.460"	2.78"	1.27"	1.51"	RED	10	100
90989	300 MCM	4/0	1.09"	0.657"	0.530"	3.08"	1.46"	1.62"	BLUE	10	100
90990	350 MCM	250	1.09"	0.704"	0.570"	3.08"	1.46"	1.62"	BROWN	10	100
90991	400 MCM	300	1.31"	0.763"	0.620"	3.38"	1.68"	1.70"	GREEN	10	100
90992	500 MCM	350	1.31"	0.842"	0.680"	3.38"	1.68"	1.70"	PINK	10	100
90993	600 MCM	400	1.46"	0.821"	0.720"	3.99"	1.72"	2.27"	YELLOW	3	30
90994	750 MCM	500	1.46"	1.03"	0.810"	4.18"	1.72"	2.46"	YELLOW	3	30

Anti-Oxidant

- For AL/AL and AL/CU Wire Connections and Aluminum Conduit Joint Threads
- For Use with All Types of Pressure Type Wire Connectors Including Compression, Screw-On, Tap, Service Entrance and Split Bolts
- Carrier Material Excludes Air to Prevent Further Oxidation
- Reduces Corrosion, Galling and Seizing
- Promotes Good Ground Continuity Through the Joint
- Improves Efficiency & Service Life of Aluminum Electrical Connections
- Temperature Range: -40°F to 302°F (-40°C to 150°C), 600 Volt
- Provides Additional Inter-Strand and Inter-Conductor Current Paths for Improved Conductivity and Cooler Connections
- Suspended Zinc Particles Penetrate and Reduce Aluminum Oxidation



CAT. NO.	SIZE	MOQ
99901	1 OUNCES	1
99904	4 OUNCES	1
99908	8 OUNCES	1