

- Manufactured from Aluminum
- Dual Rated for both Copper and Aluminum Conductors
- Electro-Tin Plated
- Rated 600V; 194°F (90°C)
- 90712-90718 & 90812-90814 Have Slotted Screws

CAT. NO.	AWG	FIG.	WIRE RANGE	DIMENSIONS			STUD SIZE	BOX QTY
				LENGTH	WIDTH	HEIGHT		
ONE CONDUCTOR - ONE HOLE MOUNT								
90712	6	1	6 STR - 14 SOL	1.06"	0.50"	0.50"	0.25"	100
90713	6	1	6 STR - 14 SOL	1.06"	0.38"	0.50"	0.25"	100
90714	2	1	2 STR - 14 SOL	1.16"	0.50"	0.55"	0.25"	100
90714B	2	1	2 STR - 14 SOL	1.16"	0.50"	0.55"	0.25"	2,000
90716	1/0	2	1/0 STR - 14 SOL	1.46"	0.63"	0.79"	0.25"	50
90716B	1/0	2	1/0 STR - 14 SOL	1.46"	0.63"	0.79"	0.25"	1,000
90718	2/0	2	2/0 STR - 14 SOL	1.46"	0.63"	0.79"	0.25"	50
90718B	2/0	2	2/0 STR - 14 SOL	1.46"	0.63"	0.79"	0.25"	1,000
90720	250	2	250 MCM - 6 SOL	2.00"	0.94"	1.12"	0.3125"	25
90720B	250	2	250 MCM - 6 SOL	2.00"	0.94"	1.12"	0.3125"	300
90722	350	2	350 MCM - 6 SOL	2.25"	1.26"	1.25"	0.375"	10
90722B	350	2	350 MCM - 6 SOL	2.25"	1.26"	1.25"	0.375"	200
90724	500	2	500 MCM - 4 SOL	2.82"	1.50"	1.57"	0.375"	10
90726	600	2	600 MCM - 2 SOL	3.19"	1.50"	1.57"	0.375"	10
90726B	600	2	600 MCM - 2 SOL	3.19"	1.50"	1.56"	0.375"	150
90728	800	2	800 MCM - 300 MCM	3.37"	1.75"	1.94"	0.625"	3
90729	1000	2	1000 MCM - 500 MCM	3.37"	1.75"	1.94"	0.625"	5

CAT. NO.	AWG	FIG.	WIRE RANGE	DIMENSIONS			STUD SIZE	BOX QTY
				LENGTH	WIDTH	HEIGHT		
ONE CONDUCTOR - TWO HOLE MOUNT								
90732	350	3	350 MCM - 6 SOL	4.22"	1.13"	1.25"	0.50"	15
90733	500	3	500 MCM - 4 SOL	4.22"	1.50"	1.57"	0.50"	6
90734	600	3	600 MCM - 2 SOL	4.22"	1.50"	1.57"	0.50"	5
90734B	600	3	600 MCM - 2 SOL	4.22"	1.50"	1.57"	0.50"	100
90735	800	3	800 MCM - 300 MCM	4.62"	1.75"	1.94"	0.50"	5
90735B	800	3	800 MCM - 300 MCM	4.62"	1.75"	1.94"	0.50"	75
90736	1000	3	1000 MCM - 500 MCM	4.62"	1.75"	1.94"	0.50"	5
90736B	1000	3	1000 MCM - 500 MCM	4.62"	1.75"	1.94"	0.50"	72
ONE CONDUCTOR - TWO HOLE MOUNT - SLOTTED MOUNTING HOLE								
90742	350	4	350 MCM - 4 SOL	3.97"	1.13"	1.25"	0.50"	5

CAT. NO.	AWG	FIG.	WIRE RANGE	DIMENSIONS			STUD SIZE	BOX QTY
				LENGTH	WIDTH	HEIGHT		
TWO CONDUCTORS - ONE HOLE MOUNT								
90812	1/0	5	1/0 STR - 14 SOL	1.34"	1.12"	0.69"	0.28"	25
90814	2/0	5	2/0 STR - 14 SOL	1.47"	1.19"	0.75"	0.28"	12
90814B	2/0	5	2/0 STR - 14 SOL	1.47"	1.19"	0.75"	0.28"	400
90816	250	6	250 MCM - 6 SOL	1.94"	1.72"	1.00"	0.41"	8
90818	350	6	350 MCM - 6 SOL	2.12"	1.88"	1.09"	0.56"	6
90818B	350	6	350 MCM - 6 SOL	2.12"	1.88"	1.09"	0.56"	150
90820	600	6	600 MCM - 2 SOL	3.19"	2.41"	1.56"	0.56"	3
90820B	600	6	600 MCM - 2 SOL	3.19"	2.41"	1.56"	0.56"	80
90822	800	6	800 MCM - 300 MCM	3.38"	2.93"	1.94"	0.66"	3
90824	1000	6	1000 MCM - 350 MCM	3.50"	3.50"	1.94"	0.66"	3
TWO CONDUCTORS - TWO HOLE MOUNT								
90841	250	7	250 MCM - 6 SOL	2.56"	1.66"	1.19"	0.50"	8
90842	350	7	350 MCM - 6 SOL	4.13"	1.91"	1.22"	0.50"	6
90844	600	7	600 MCM - 2 SOL	4.65"	2.41"	1.51"	0.56"	3
90844B	600	7	600 MCM - 2 SOL	4.65"	2.41"	1.51"	0.56"	50
90845	800	7	800 MCM - 1/0 STR	4.75"	2.75"	1.69"	0.56"	3
90845B	800	7	800 MCM - 1/0 STR	4.75"	2.75"	1.69"	0.56"	32



FIG. 1



FIG. 2



FIG. 3




FIG. 4



FIG. 5




FIG. 6



FIG. 7