



- Manufactured from Copper
- Rated for Copper Conductors Only
- Connectors are Re-Usable
- Rated 600V; 194°F (90°C)

CAT. NO.	AWG	MAX RUN TO MAX TAP	MIN RUN TO MIN. TAP	MAX RUN TO MIN TAP	MIN EQUAL TAP & RUN	TORQUE IN LB	DIMENSIONS				BOX QTY
							A	B	C	D	
90301	8	8 - 8	16 - 16	8 - 16	16 - 16	80	0.472"	0.145"	0.562"	0.854"	100
90302	6	6 - 6	10 - 16	6 - 16	10 - 10	165	0.492"	0.165"	0.625"	0.906"	100
90303	4	4 - 4	8 - 16	4 - 16	8 - 8	165	0.709"	0.268"	0.812"	1.16"	50
90304	3	2 - 2	4 - 8	2 - 8	4 - 4	275	0.600"	0.260"	0.750"	1.50"	50
90305	2	2 - 2	6 - 14	2 - 14	6 - 6	275	0.748"	0.326"	0.812"	1.26"	50
90306	1/0	1/0 - 1/0	4 - 14	1/0 - 14	4 - 4	385	0.787"	0.374"	0.937"	1.54"	50
90307	2/0	2/0 - 2/0	2 - 14	2/0 - 14	2 - 2	385	0.866"	0.421"	1.06"	1.69"	25
90308	3/0	3/0 - 3/0	2 - 8	3/0 - 8	2 - 2	500	1.10"	0.531"	1.25"	2.09"	25
90309	4/0 - 250	250 - 250	1/0 - 8	250 - 8	1/0 - 1/0	650	1.10"	0.579"	1.25"	2.09"	25
90310	350	350 - 350	4/0 - 1/0	350 - 1/0	4/0 - 4/0	650	1.22"	0.700"	1.50"	2.36"	12
90311	500	500 - 500	250 - 2/0	500 - 2/0	250 - 250	825	1.34"	0.815"	1.75"	2.84"	12
90312	750	750 - 750	350 - 4/0	750 - 4/0	350 - 350	1000	1.94"	1.02"	2.31"	3.51"	1