

Copper C-Taps

- Applications Include Copper to Copper Tapping, Splicing or Stub/Pigtail
- High Strength Electrolytic Copper
- Allows for 2 Continuous Parallel Conductors
- Compact Size & Range Taking



FIG. 1



FIG. 2

CAT. NO.	FIG.	DIE COLOR	CONDUCTOR RANGE		DIMENSIONS					BOX QTY
			RUN	TAP	STRIP L	L	W (ID)	H	T	
91802	1	RED	14	16-14	1/2"	0.32"	0.18"	0.16"	0.07"	275
			12	16-12						
			10	14						
91803	1	BLUE	10	10	5/8"	0.61"	0.32"	0.36"	0.07"	275
			8	12						
			6	10-12						
91804	1	GRAY	8	8-10	5/8"	0.61"	0.32"	0.43"	0.07"	200
			6	10-12						
			8	8-10						
91805	1	BROWN	4	8-10-12	1-1/4"	1.17"	0.41"	0.43"	0.07"	150
			6	6-8						
			4	6-4						
91806	1	GREEN	3	12-6	1-1/4"	1.17"	0.45"	0.52"	0.07"	100
			4	6-4						
			3	12-6						
91807	1	PINK	4	4	1-1/4"	1.17"	0.49"	0.54"	0.07"	100
			3	4-6						
			2	12-6						
91808	1	BLACK	1	12-4	2"	1.75"	0.53"	0.64"	0.07"	100
			2	4-6						
			3	4-3						
91809	1	ORANGE	1/0	12-4	2"	1.75"	0.61"	0.71"	0.09"	50
			1	4-3						
			2	4-2						
91810	1	PURPLE	2/0	12-4	2"	1.75"	0.69"	0.77"	0.09"	30
			1/0	2						
			1	1-2						
91811	1	YELLOW	3/0	2-12	1"	1.75"	0.81"	1.07"	0.09"	30
			2/0	1-2						
			1/0	1/0-1						

CAT. NO.	FIG.	DIE COLOR	CONDUCTOR RANGE		DIMENSIONS					BOX QTY
			RUN	TAP	STRIP L	L	W (ID)	H	T	
91812	2	YELLOW	1	1	1"	1.30"	0.79"	0.63"	0.16"	50
			1/0	1/0-2						
			2/0	2/0-4						
91813	2	BLUE	3/0	1/0-6	1"	1.46"	0.79"	0.79"	0.20"	50
			4/0	1-8						
			2/0	2/0-1						
91814	2	BLUE	3/0	3/0-3	1"	1.46"	0.79"	0.79"	0.20"	50
			4/0	4/0-4						
			250	1/0-8						
91815	2	BROWN	2/0	2/0-1	1-1/8"	1.67"	1.03"	.85"	0.20"	25
			3/0	3/0-3						
			4/0	4/0-4						
91816*	2	BROWN 600 MCM BLACK 750 MCM	250	250	1-5/16"	1.87"	1.28"	1.02"	0.20"	15
			300	300-3/0						
			350	350-1/0						
91817*	2	WHITE	400	300-2	1-5/16"	2.17"	1.29"	1.18"	0.30"	10
			450	250-4						
			500	250-6						
91818*	2	-	350	350-4/0	2-3/4"	2.75"	1.97"	1.34"	0.16"	5
			400	400-2/0						
			450	450-1						
91819*	2	-	500	500-2	2-3/4"	2.75"	1.97"	1.34"	0.16"	5
			750	750-4/0						
			750	750-4/0						

*NOT LISTED FOR DIRECT BURIAL, GROUNDING OR BONDING

- Heavy Wall High Strength Electrolytic Copper
- Allows for 2 Continuous Parallel Conductors
- Range Taking



CAT. NO.	CONDUCTOR RANGE		DIE TYPE	DIMENSIONS				ENTRY	STRIP LENGTH	BOX QTY
	RUN MAX	TAP MAX		L (OD)	L (ID)	W	D			
91819	6-6	6-6	BG	0.77"	0.46"	0.71"	0.43"	0.29"	3/4"	50
91820	6-4	4-4	BG	0.81"	0.53"	0.63"	0.47"	0.31"	3/4"	25
91821	2-2	8-4	C	0.98"	0.65"	0.75"	0.61"	0.37"	3/4"	50
91822	2-2	2-2	C	1.05"	0.76"	0.76"	0.60"	0.45"	3/4"	50
91823	1/0-2/0	1/0-2/0	C	1.35"	0.87"	0.95"	0.80"	0.43"	1-1/8"	25
91824	3/0-4/0	1/0-2/0	D3	1.64"	1.01"	1.07"	0.97"	0.60"	1-1/4"	15
91825	3/0-4/0	3/0-4/0	D3	1.58"	1.10"	1.07"	0.97"	0.56"	1-1/4"	15