



UF Direct Burial Splice Kits - Heat Shrink

- Labor savings - simplifies splicing UF cable by obsoleting messy multi part splicing kits. Seal with heat gun or torch
- Provides a reliable, moisture proof electrical connection for UF cable
- 14/3 or 12/3 minimum to 8/3 maximum
- Comes complete with one 4-position brass connector and one 8" piece of adhesive/sealant lined heat shrink tubing
- UL486D Listed Submersible & Raintight, 600 Volt 221°F (105°C)



CAT. NO.	DESCRIPTION	BAG QTY
67000	14 - 8 AWG UF DIRECT BURIAL SPLICE KIT	1

Direct Burial UF In-Line Splice Kit - EPDM Rubber Cover

- Perfect for 14/2, 14/3, 12/2, 12/3, 10/2, 10/3 UF Cable Applications
- No Taping, Mixing, Mastics or Heat Gun Required
- Specially designed UF Adaptor Opening Molded into Cover
- Waterproof, Submersible & Re-Enterable, UV Resistant
- Connector Included



CAT. NO.	WIRE RANGE	CONNECTOR		COVER		CASE QTY
		DIAMETER	LENGTH	DIAMETER	LENGTH	
67056	14/2 - 10/3	0.86"	1.81"	1.63"	8.31"	5

Direct Burial Dual Rated Splice Kits - Heat Shrink

- Eliminates Expensive Crimping Tools when Splicing Aluminum or Copper Conductors for Direct Burial
- Kit comes complete with one mechanical connector and one piece of heat shrink tubing
- For Repair and/or Extending type USE or Other Electrical Cable
- Seal with Heat Gun or Torch
- UL Listed Components, 600 Volt Maximum 221°F (105°C) Rating

CAT. NO.	FIG.	DESCRIPTION	BAG QTY
67002	1	8 - 2 AWG DUAL RATED BUTT SPLICE	1
67004	1	6 - 1/0 AWG DUAL RATED BUTT SPLICE	1
67003	1	8 - 2/0 AWG DUAL RATED BUTT SPLICE	1
67005	1	3/0 - 250 MCM AWG DUAL RATED BUTT SPLICE	1
67006	2	3/0 - 250 MCM AWG DUAL RATED BUTT SPLICE	1



FIG. 1

FIG. 2

Direct Burial Mechanical Splice Kits - EPDM Rubber Cover

- Prevents oxidation and keeps out moisture
- Approved for use with Aluminum or Copper Conductors
- Perfect for repairing any 2, 3, or 4-wire installation
- Direct Burial & Submersible - Ensure a fully insulated, Water-tight Splice Repair - No taping or Heat Shrink or mastic required
- 600V, Meets or Exceeds C119.4, RUS Accepted



CAT. NO.	WIRE RANGE AWG	SCREW CONFIGURATION	CONNECTOR		COVER		CASE QTY
			DIAMETER	LENGTH	DIAMETER	LENGTH	
67058	#6 - 350 MCM	2 SCREW	1.13"	2.56"	1.55"	10.45"	25
67060	#6 - 350 MCM	4 SCREW	1.13"	4.06"	1.55"	10.45"	25

Direct Burial Splice Covers - EPDM Rubber

- For Direct Burial, Underground Vault, Overhead Service Splices
- Approved for Aluminum or Copper Conductors, Connector Not Included
- Ensures a Fully Insulated, Water-Tight Repair Splice - No Taping, Heat Shrink or Mastic Required, 600V, REA Approved



CAT. NO.	WIRE RANGE AWG	WIRE RANGE DIAMETER	DIMENSIONS		CASE QTY
			DIAMETER	LENGTH	
67052	#14 - 2/0	0.15" - 0.60"	1.01"	5.97"	250
67053	#14 - 350	0.15" - 0.98"	1.27"	8.25"	100

