

Thin Wall Heat Shrink Tubing - 6" length



- Flexible Polyolefin Heat Shrink Tubing
- 2:1 Shrink Ratio
- 600 Volt
- 257°F (125°C) Continuous Operation
- For Insulating, Wire Harness, Wire Bundling, Splicing & Terminations
- UL 224 Recognized

CAT NO.	LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	BAG QTY
68030	6"	BLACK	0.078"	0.029"	50
68032	6"	BLACK	0.098"	0.039"	50
68034	6"	BLACK	0.137"	0.059"	50
68036	6"	BLACK	0.211"	0.098"	10
68038	6"	BLACK	0.250"	0.117"	10
68040	6"	BLACK	0.367"	0.176"	10
68042	6"	BLACK	0.484"	0.234"	10
68044	6"	BLACK	0.827"	0.390"	10
68046	6"	BLACK	1.26"	0.590"	10
68323	6"	CLEAR	0.098"	0.039"	50
68325	6"	CLEAR	0.211"	0.098"	10
68326	6"	CLEAR	0.250"	0.117"	10
68327	6"	CLEAR	0.367"	0.176"	10
68328	6"	CLEAR	0.484"	0.234"	10
68329	6"	CLEAR	0.827"	0.390"	10
68331	6"	RED	0.078"	0.029"	50
68332	6"	RED	0.098"	0.039"	50
68333	6"	RED	0.137"	0.059"	50
68334	6"	RED	0.211"	0.098"	10
68336	6"	RED	0.367"	0.176"	10
68337	6"	RED	0.484"	0.234"	10
68338	6"	RED	0.827"	0.390"	10
68339	6"	RED	1.26"	0.590"	10
68340	6"	GREEN	0.078"	0.029"	50
68342	6"	GREEN	0.137"	0.059"	50
68343	6"	GREEN	0.211"	0.098"	10
68344	6"	GREEN	0.250"	0.117"	10
68348	6"	GREEN	1.26"	0.590"	10
68349	6"	WHITE	0.078"	0.029"	50
68351	6"	WHITE	0.137"	0.059"	50
68352	6"	WHITE	0.211"	0.098"	10
68353	6"	WHITE	0.250"	0.117"	10
68354	6"	WHITE	0.367"	0.176"	10
68355	6"	WHITE	0.484"	0.234"	10
68356	6"	WHITE	0.827"	0.390"	10
68357	6"	WHITE	1.26"	0.590"	10
68359	6"	BLUE	0.098"	0.039"	50
68360	6"	BLUE	0.137"	0.059"	50
68361	6"	BLUE	0.211"	0.098"	10
68362	6"	BLUE	0.250"	0.117"	10
68363	6"	BLUE	0.367"	0.176"	10
68364	6"	BLUE	0.484"	0.234"	10
68366	6"	BLUE	1.26"	0.590"	10