



- Submersible Rated for Cable Jacket Repair & Splicing
- Conforms to ANSI C119.1 1986
- Silicone Rubber Jacketing Material
- Durable Tear Resistant Removable Rip-Cord Core
- 1000V Rated for Primary Insulation
- UV Resistant



Cold Shrink

CAT. NO.	CONDUCTOR RANGE	APPLICATION RANGE	LENGTH	VOLTAGE	BAG QTY	CASE QTY
68302	#2 - 1/0	0.37" - 0.57"	8"	1000	1	10
68304	2/0 - 400	0.57" - 1.35"	9"	1000	1	10
68306	500 - 800	0.97" - 1.95"	9"	1000	1	10
68308	500 - 800	0.97" - 1.95"	12"	1000	1	10
68310	900 - 1000	1.32" - 2.65"	9"	1000	1	10

Heat Shrink End Caps

- Simple & effective method for sealing cable ends, pipe & conduit
- Superior Resistance to Weathering, Moisture Contamination, Adverse Environmental Conditions & Common Fluid/Solvents
- Adhesive Liner provides complete environmental protection & insulation
- Heat Indicating Lines
- Continuous Operating Temperature -67°F to 230°F (-55°C to 110°C)
- Rated to 1KV 194°F (90°C) Continuous Use
- UL486D - Shrink Temperature of 248°F (120°C)
- Black Color

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68232	2 - 4/0	3.50"	0.75"	0.22"	0.08"
68234	300 - 1000 MCM	4.00"	1.30"	0.40"	0.08"
68236	500 - 1500 MCM	4.50"	1.50"	0.50"	0.08"
68238	900 - 2500 MCM	4.50"	2.05"	0.75"	0.08"
68240	2000 - 2500 MCM	5.00"	2.75"	1.00"	0.08"



Medium Wall Heat Shrink Tubing - 3:1 Shrink Ratio

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68112	12 - 6	4'	0.40"	0.15"	0.080"
68114	8 - 1/0	4'	0.75"	0.22"	0.080"
68116	2 - 4/0	4'	1.10"	0.40"	0.080"
68118	-	4'	1.30"	0.40"	0.080"
68120	3/0 - 400	4'	1.50"	0.50"	0.080"
68122	-	4'	1.70"	0.50"	0.080"
68124	250 - 750	4'	2.05"	0.75"	0.080"
68126	-	4'	2.75"	1.00"	0.080"
68128	800 - 1250	4'	3.50"	1.18"	0.095"
68130	1500 - 2500	4'	4.70"	1.57"	0.105"
68132	-	4'	6.70"	2.30"	0.110"
ROLLS					
68142	12 - 6	50'	0.40"	0.15"	0.080"
68144	8 - 1/0	25'	0.75"	0.22"	0.080"
68146	2 - 4/0	25'	1.10"	0.40"	0.080"
68148	3/0 - 400	50'	1.50"	0.50"	0.080"
68150	-	50'	1.70"	0.50"	0.080"
68152	250 - 750	25'	2.05"	0.75"	0.080"



- 3:1 Shrink Ratio
- Suitable for Electrical and Mechanical Applications where Lighter Weight and Flexibility are Important
- Seals and Protects Cable Splices and Terminations
- High Resistance to Impact and Abrasion
- 4' Lengths have Adhesive Liner for Complete Environmental Protection and Insulation
- Continuous Operating Temperature:
 - -67°F to 230°F (-55°C to 110°C)
- Shrink Temperature: 248°F (120°C)
- Rated for 600-1000V
- Black Color