



Heavy Wall Heat Shrink Tubing



- 3:1 Shrink Ratio
- Provides maximum reliability for insulating and protection of cable joints and terminations
- Corrosion and Chemical Resistance
- Rated for 600-1000V, 90°C Continuous Use
- 4 FT Lengths have Thermoplastic Adhesive Liner
- Continuous operating temperature: -67°F to 230°F
- Shrink temperature: 248°F (120°C)
- Heavy Wall holds better mechanically & has better underground protection than medium wall
- Black color

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68162	#14 - #10	4'	0.35"	0.12"	.07
68164	#8 - #6	4'	0.51"	0.16"	.09
68166	#6 - #2	4'	0.75"	0.24"	.09
68168	#1 - #3/0	4'	1.10"	0.35"	.12
68170	2/0 - 350	4'	1.50"	0.47"	.16
68172	250 - 500	4'	2.00"	0.63"	.16
68174	600 - 1000	4'	2.70"	0.87"	.16
68176	800 - 1250	4'	3.54"	1.18"	.16
68178	1500 - 2500	4'	4.72"	1.57"	.17
ROLLS					
68182	#14 - #10	25'	0.35"	0.12"	.07
68186	#6 - #2	25'	0.75"	0.24"	.09
68188	#1 - 3/0	25'	1.10"	0.35"	.12
68190	2/0 - 350	25'	1.50"	0.47"	.16
68192	250 - 500	25'	2.00"	0.63"	.16
68194	600 - 1000	25'	2.70"	0.87"	.16
68196	800 - 1250	25'	3.54"	1.18"	.16

Heavy Wall Heat Shrink Tubing - Flame Retardant



- 3:1 Shrink Ratio allows Various Shapes & Contours to be Accommodated
- Insulates & Protects Electrical Splices & terminations where maximum flame retardants is required
- Adhesive sealant liner provides complete environmental protection and insulation
- Will Not Split or Rupture during installation
- Flame Retardant
- Rated for 1KV, 90°C continuous use
- Continuous operating temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink temperature: 248°F (120°C)
- Black color

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
6" LENGTHS					
68004	1 - 8 AWG	6"	0.40"	0.13"	0.09"
68008	6 - 2 AWG	6"	0.75"	0.24"	0.09"
68011	1 - 3/0 AWG	8"	1.10"	0.35"	0.12"
68012	1 - 3/0 AWG	12"	1.10"	0.35"	0.12"
68015	2/0 - 350 MCM	8"	1.50"	0.47"	0.16"
68020	250 - 500 MCM	12"	2.00"	0.63"	0.16"
4' LENGTHS					
68022	12 - 8 AWG	4'	0.40"	0.13"	0.09"
68023	6 - 2 AWG	4'	0.75"	0.24"	0.09"
68024	1 - 3/0 AWG	4'	1.10"	0.35"	0.12"
68025	2/0 - 350 MCM	4'	1.50"	0.47"	0.16"
68026	250-500 MCM	4'	2.00"	0.63"	.16