


Aluminum Long Barrel 2 Hole Compression Lugs

- AL9CU Listed - For Both Aluminum and Copper Conductors
- Pre-filled with Oxide Inhibitor
- Made of High-Conductivity Seamless Aluminum
- Electro-Tin Plating Resists Corrosion
- Dual Mounting Holes for Superior Contact Integrity
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486AB Listed for Applications Thru 35KV



CAT. NO.	WIRE RANGE	STUD SIZE	COLOR CODE	DIMENSIONS										BOX QTY
				A	C	J	B	D	F	E	G	PL	S	
93110	1/0 STR.	3/8"	TAN	0.39"	0.63"	3.50"	1.20"	0.85"	0.24"	0.41"	0.38"	1.87"	1.00"	10
93111	1/0 STR.	1/2"	TAN	0.39"	0.63"	4.75"	1.20"	0.85"	0.24"	0.51"	0.63"	3.12"	1.75"	20
93109	2/0 STR.	3/8"	OLIVE	0.44"	0.69"	4.80"	1.30"	0.94"	0.24"	0.41"	0.63"	3.12"	1.00"	20
93112	2/0 STR.	1/2"	OLIVE	0.44"	0.69"	4.80"	1.30"	0.94"	0.24"	0.51"	0.63"	3.12"	1.75"	20
93113	3/0 STR.	3/8"	RUBY	0.48"	0.76"	5.00"	1.40"	1.03"	0.28"	0.41"	0.63"	3.12"	1.00"	20
93114	3/0 STR.	1/2"	RUBY	0.48"	0.76"	5.00"	1.40"	1.03"	0.28"	0.51"	0.63"	3.12"	1.75"	20
93115	4/0 STR.	3/8"	WHITE	0.55"	0.84"	5.25"	1.40"	1.15"	0.29"	0.41"	0.63"	3.12"	1.00"	12
93116	4/0 STR.	1/2"	WHITE	0.55"	0.84"	5.25"	1.40"	1.15"	0.29"	0.51"	0.63"	3.12"	1.75"	12
93117	250 MCM	3/8"	RED	0.59"	0.92"	5.31"	1.50"	1.26"	0.32"	0.41"	0.63"	3.12"	1.00"	12
93118	250 MCM	1/2"	RED	0.59"	0.92"	5.31"	1.50"	1.26"	0.32"	0.51"	0.63"	3.12"	1.75"	12
93119	300 MCM	3/8"	BLUE	0.65"	1.01"	5.50"	1.60"	1.37"	0.35"	0.41"	0.63"	3.12"	1.00"	9
93120	300 MCM	1/2"	BLUE	0.65"	1.01"	5.50"	1.60"	1.37"	0.35"	0.51"	0.63"	3.12"	1.75"	9
93121	350 MCM	3/8"	BROWN	0.72"	1.12"	5.87"	1.90"	1.52"	0.39"	0.41"	0.63"	3.12"	1.00"	6
93122	350 MCM	1/2"	BROWN	0.72"	1.12"	5.87"	1.90"	1.52"	0.39"	0.51"	0.63"	3.12"	1.75"	6
93123	400 MCM	3/8"	GREEN	0.76"	1.19"	6.43"	2.30"	1.61"	0.42"	0.41"	0.63"	3.12"	1.00"	6
93124	400 MCM	1/2"	GREEN	0.76"	1.19"	6.43"	2.30"	1.61"	0.42"	0.51"	0.63"	3.12"	1.75"	6
93125	500 MCM	3/8"	PINK	0.84"	1.32"	6.50"	2.50"	1.79"	0.47"	0.41"	0.63"	3.12"	1.00"	6
93126	500 MCM	1/2"	PINK	0.84"	1.32"	6.50"	2.50"	1.79"	0.47"	0.51"	0.63"	3.12"	1.75"	6
93127	500 MCM	5/8"	PINK	0.84"	1.32"	6.50"	2.50"	1.79"	0.47"	0.67"	0.63"	3.12"	1.75"	6
93129	600 MCM	3/8"	BLACK	0.92"	1.44"	6.75"	2.60"	1.96"	0.51"	0.41"	0.63"	3.12"	1.00"	4
93128	600 MCM	1/2"	BLACK	0.92"	1.44"	6.75"	2.60"	1.96"	0.51"	0.51"	0.63"	3.12"	1.75"	4
93131	600 MCM	5/8"	BLACK	0.92"	1.44"	6.75"	2.60"	1.96"	0.51"	0.67"	0.63"	3.12"	1.75"	4
93132	750 MCM	3/8"	YELLOW	1.03"	1.60"	7.37"	3.20"	2.19"	0.55"	0.41"	0.63"	3.12"	1.00"	4
93130	750 MCM	1/2"	YELLOW	1.03"	1.60"	7.37"	3.20"	2.19"	0.55"	0.51"	0.63"	3.12"	1.75"	4
93133	750 MCM	5/8"	YELLOW	1.03"	1.60"	7.37"	3.20"	2.19"	0.55"	0.67"	0.63"	3.12"	1.75"	4

Aluminum Long Barrel Compression Splices



- AL9CU Listed - for both Aluminum and Copper Conductors
- Pre-filled with Oxide Inhibitor
- Made of High-Conductivity Seamless Aluminum
- Electro-Tin Plating Resists Corrosion
- Color Coded Die Index and Crimp Marks Printed on Barrel
- UL 486AB Listed for Applications Thru 35KV

CAT. NO.	WIRE RANGE	COLOR CODE	DIMENSIONS			BOX QTY
			A	C	LENGTH (L)	
93208	8 STR.	BLUE	0.16"	0.30"	1.38"	50
93210	6 STR.	GRAY	0.20"	0.34"	1.63"	50
93212	4 STR.	GREEN	0.25"	0.44"	2.00"	30
93214	2 STR.	PINK	0.31"	0.53"	2.38"	30
93216	1 STR.	GOLD	0.35"	0.53"	2.38"	15
93218	1/0 STR.	TAN	0.39"	0.63"	2.50"	20
93220	2/0 STR.	OLIVE	0.44"	0.69"	2.63"	20
93222	3/0 STR.	RUBY	0.48"	0.76"	2.88"	15
93224	4/0 STR.	WHITE	0.55"	0.84"	3.13"	10
93226	250 MCM	RED	0.59"	0.92"	3.25"	9
93228	300 MCM	BLUE	0.65"	1.01"	3.25"	9
93230	350 MCM	BROWN	0.72"	1.12"	3.88"	6
93232	400 MCM	GREEN	0.76"	1.19"	4.88"	6
93234	500 MCM	PINK	0.84"	1.32"	5.00"	6
93236	600 MCM	BLACK	0.92"	1.44"	5.13"	4
93238	750 MCM	YELLOW	1.03"	1.60"	5.38"	4