Heavy Duty Ground Rod Clamps - Direct Burial



- Designed to Maintain Proper Contact and Alignment between Ground Wire & Ground Rod
- Listed for use with Copper Bonded Steel, Stainless Steel and Galvanized Ground Rods
- Cast of High Strength Copper Alloy containing 80% or more Copper
- Silicone Bronze or Stainless Steel Bolt
- UL 467 Approved for Direct Burial in Soil & Concrete
- Direct Burial Marked on Clamps




DIMENSIONS = INCHES

CAT.	ROD	REBAR SIZE	WIRE	SCREW THREAD SIZE	DIMENSIONS		BOX
NO.	DIAMETER	KLDAK SIZL	RANGE		Α	В	ŌΤŸ
90634	1/2"	3/8″	#2-#10	5/16-18	.50	1.24	50
90636	5/8"	1/2"	1/0-#10	3/8-16	.59	1.46	50
90638	3/4"	5/8″	#1-#10	3/8-16	.59	1.51	50
90639	1/2", 5/8", 3/4"	3/8", 1/2", 5/8"	1/0-#10	3/8-16	.59	2.38	50
90535	1"	-	4/0-#8	3/8-16	.58	2.40	50

Copper Ground Pipe Clamps



- For Connecting Grounding Conductor to Water Pipe,
 Copper Tubing or Ground Rod
- Cast of High Strength High Conductivity Copper Alloy
- Steel Set Screws Zinc Plated for Corrosion Resistance





DIMENSIONS = INCHES

CAT.	WATER PIPE RANGE	WIRE RANGE	SCREW THREAD SIZE	DIMENSIONS		BOX
NO.				Α	В	BOX QTY
90627	1/2"-1"	2-10	1/4-20	2.25	1.64	25
90628	1-1/4"-2"	2-10	5/16-18	3.54	2.48	10
90598	2-1/2"-4"	2-10	3/8-16	6.30	3.40	15
90599	4-1/2"-6"	2-10	3/8-16	8.30	4.00	5

Conduit Hub Adaptors

- Conduit Hub Adaptors Used with Standard Ground Pipe Clamps to Ground Conduit to Pipe - Used with 90627, 90628, 90598 & 90599 Pipe Clamps
- Allows for Maximum Flexibility In the Field
- Cast of High Strength, High Conductivity Copper Alloy
- For Grounding Water Pipe to Electrical Conduit
- \bullet Can also purchase pre-assembled Clamp & Adaptors 90601 Thru 90606

CAT. No.	CONDUIT Size	BOX QTY		
91600	1/2"	10		
91601	3/4"	10		
91602	<u> </u> "	10		

