
Copper Ground Pipe Clamps - Direct Burial







- For Grounding Conductors to Water Pipe, Copper Tubing or Ground Rod
- 90631 UL Direct Burial Clamp Designed for Copper-to-Rebar
- Commonly used for Swimming Pools/Spas, Commercial, Industrial & Agricultural Applications
- Cast of High Strength, High Conductivity Copper Alloy
- 90621 & 90622 Have Copper Screws
- 90629, 90630 & 90631 Have Stainless Steel Screws
- UL 467 Listed for Direct Burial in Soil or Concrete

DIMENSIONS = INCHES

NO. RANGE ROD SIZE SIZE RANGE THREAD THREAD A B 90629 1/2"-I" I" - 2-I0 1/4-20 1/4-20 2.17 142 90630 1-1/4"-2" I" - 2-I0 1/4-20 5/16-18 3.58 1.93 90621 2-1/2"-4" 2" - 2-I0 1/4-20 5/16-18 5.95 2.95 90622 4-1/2"-6" 2" - 2-I0 1/4-20 5/16-18 8.09 4.19 PIPE CLAMPS FOR REBAR APPLICATIONS PIPE CLAMPS FOR REBAR APPLICATIONS	CAT.	WATER PIPE	GROUND	REBAR	WIRE	TOP SCREW	SIDE SCREW	DIMEN	SIONS	BOX
90630 1-1/4"-2" 1" - 2-10 1/4-20 5/16-18 3.58 1.93 90621 2-1/2"-4" 2" - 2-10 1/4-20 5/16-18 5.95 2.95 90622 4-1/2"-6" 2" - 2-10 1/4-20 5/16-18 8.09 4.19 PIPE CLAMPS FOR REBAR APPLICATIONS	NO.	RANGE	ROD SIZE	SIZE	RANGE	THREAD	THREAD	Α	В	QΤY
9062 2-1/2"-4" 2" - 2-10 1/4-20 5/16-18 5.95 2.95 90622 4-1/2"-6" 2" - 2-10 1/4-20 5/16-18 8.09 4.19 PIPE CLAMPS FOR REBAR APPLICATIONS	90629	1/2"-1"	۱"	-	2-10	1/4-20	1/4-20	2.17	1.42	25
90622 4-1/2"-6" 2" - 2-10 1/4-20 5/16-18 8.09 4.19 PIPE CLAMPS FOR REBAR APPLICATIONS	90630	1-1/4"-2"	l "	-	2-10	1/4-20	5/16-18	3.58	1.93	10
PIPE CLAMPS FOR REBAR APPLICATIONS	90621	2-1/2"-4"	2"	-	2-10	1/4-20	5/16-18	5.95	2.95	5
	90622	4-1/2"-6"	2"	-	2-10	1/4-20	5/16-18	8.09	4.19	5
0.0631 1/3"-1" 1/4"-1" 3/9"-1" 2-10 1/4-20 1/4-20 2.25 1.64				PIPE CLAM	PS FOR REBAR	APPLICATIONS				
30001 1/2 1 1/4 1 3/0 1 2 10 1/4 20 1/4 20 2.20 1.04	90631	1/2 "-1"	1/4"-1"	3/8"-I"	2-10	1/4-20	1/4-20	2.25	1.64	25

Copper Ground Pipe Clamps - Serrated Collar 👊





- Serrated Collar Accommodates a Variety of Adaptors for Maximum Flexibility In the Field
- High Strength, High Conductivity Copper Alloy
- Zinc Plated Steel Set Screws for Corrosion Resistance
- Use with Morris Cat# 91603 thru 91606 Serrated Adaptors for Armored Cable or Conduit Grounding Applications

DIMENSIONS = INCHES

					DIFFERENCIATE INTERES
	CAT.	PIPE	WIRE	BOX	
	NO.	RANGE	MIN	MAX	— BOX QTY
	91660	1/2"-1"	10 SOL	2 STR	10
	91662	I-I/4"-2"	IO SOL	2 STR	10
Ξ	91664	2-1/2 "-4"	IO SOL	2 STR	35
	91666	4-1/2 "- 6"	IO SOL	2 STR	25

Serrated Adaptors - for Serrated Collar Ground Clamps



FIG 1

- Serrated Teeth match Serrated Collar Pipe Clamps for maximum flexibility in the Field
- Use with Serrated Collar Pipe Clamps Cat# 91660 Thru 91666
- For Grounding Pipe to Electrical Conduit or Ground Wires
- Cast of High Strength, High Conductivity Copper Alloy
- Can also purchase pre-assembled Clamp & Adaptors Cat #91701 Thru 91709 or Cat# 91690 Thru 91696



FIG 2

CAT.	FIGURE	CONDUIT SIZE	WIRE	WIRE RANGE	
NO.			MIN	MAX	BOX QTY
	SER	RATED CONDUIT H	JB ADAPTOR		
91603	1	1/2"	N/A	N/A	25
91604	1	3/4"	N/A	N/A	25
91605	1	1"	N/A	N/A	25
	SERR	ATED ARMORED CA	BLE ADAPTOR		
91606	2	N/A	#8	4/0	25