

Copper Ground Clamps - Rotatable - Rigid Conduit Hub



- For Connecting Electrical Conduit to Water Pipe, Copper Tubing & Ground Rod
- Serrated Conduit Adaptor Swings 360° for Easy Alignment
- Cast of High Strength High Conductivity Copper Alloy
- Steel Set Screws Zinc Plated for Corrosion Resistance



DIMENSIONS = INCHES

CAT. NO.	PIPE SIZE	HUB SIZE	WIRE RANGE		DIMENSIONS		SCREW TYPE		BOX QTY
			MIN	MAX	LENGTH	HEIGHT	TOP	SIDE	
91701	1/2 - 1	1/2	10 STR	4 STR	2.17	1.95	3/16"-24 X 1.37	5/16"-18 X 1.69	10
91702	1/2 - 1	3/4	10 STR	2/0 STR	2.17	2.15	3/16"-24 X 1.37	1/4"-20 X 1.67	10
91703	1/2 - 1	1	10 STR	3/0 STR	2.24	2.32	3/16"-24 X 1.37	1/4"-20 X 1.67	10
91704	1-1/4 - 2	1/2	10 STR	4 STR	3.58	2.54	3/16"-24 X 1.37	5/16"-18 X 2.60	5
91705	1-1/4 - 2	3/4	10 STR	2/0 STR	3.58	3.68	3/16"-24 X 1.50	5/16"-18 X 2.60	5
91706	1-1/4 - 2	1	10 STR	3/0 STR	3.58	3.81	3/16"-24 X 1.50	5/16"-18 X 2.60	5
91707	2-1/2 - 4	1/2	10 STR	4 STR	5.95	4.00	3/16"-24 X 1.50	5/16"-18 X 4.23	5
91708	2-1/2 - 4	3/4	10 STR	2/0 STR	5.95	4.20	3/16"-24 X 1.50	5/16"-18 X 4.23	5
91709	2-1/2 - 4	1	10 STR	3/0 STR	5.95	4.33	3/16"-24 X 1.50	5/16"-18 X 4.23	5

Copper Ground Clamps - Rigid Conduit Hub



- Suitable for connecting grounding conductor in rigid conduit to water pipe, ground rod and copper weld tubing
- Standard Collar and Adaptor
- Hub Swings 360° for Easy Alignment
- Cast of High Strength High Conductivity Copper Alloy
- Steel Set Screws are Zinc Plated for Corrosion Resistance
- UL Listed



DIMENSIONS = INCHES

CAT. NO.	PIPE RANGE	CONDUIT SIZE	CONDUCTOR		DIMENSIONS		TOP SCREW SIZE	SIDE SCREW SIZE	BOX QTY
			MIN	MAX	LENGTH	WIDTH			
90601	1/2 - 1	1/2	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10
90602	1/2 - 1	3/4	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10
90603	1/2 - 1	1	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10
90604	1-1/4 - 2	1/2	10	2	3.58	2.48	5/16-18 X .73	5/16-18 X 2.25	5
90605	1-1/4 - 2	3/4	10	2	3.58	2.48	5/16-18 X .73	5/16-18 X 2.25	5
90606	1-1/4 - 2	1	10	2	3.58	2.48	5/16-18 X .73	5/16-18 X 2.25	5

Copper Ground Clamps - Rigid Conduit Hub & Strap

NEW



- Suitable for connecting grounding strap to rigid conduit to water pipe, ground rod and copper weld tubing
- 1/2" or 3/4" Conduit hub & extension strap
- 8" Copper Strap & Hub Swing 360° for Easy Alignment
- Cast of High Strength High Conductivity Copper Alloy
- Steel Set Screws are Zinc Plated for Corrosion Resistance
- 91558 for water heater applications has 2 pipe clamps & 24" of 6 awg copper wire included
- UL Listed

**AVAILABLE
JULY 2020**



FIG 1



FIG 2

DIMENSIONS = INCHES

CAT. NO.	FIG	PIPE RANGE	CONDUIT SIZE	CONDUCTOR		DIMENSIONS		TOP SCREW SIZE	SIDE SCREW SIZE	BOX QTY
				MIN	MAX	LENGTH	WIDTH			
91550	1	1/2 - 1	1/2	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10
91556	1	1/2 - 1	3/4	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10
91558	2	1/2 - 1	N/A	10	2	2.24	1.52	1/4-20 X .63	1/4-20 X 1.50	10