

Copper Ground Pipe Clamps - Lay-In



GROUNDING Lay-In Pipe Clamps



FIG 1



FIG 2



FIG 3

- For Connecting Grounding Conductors to Water Pipe, Conduit, Copper Tubing, Ground Rods or Rebar
- Parallel, Perpendicular or Top Entry Lay-In Feature for Easy Wire Insertion in Continuous Loop applications
- Cast of High Strength Copper Alloy containing 80% or more Copper
- Copper or Stainless Steel Screws
- UL 467 Listed for Direct Burial in Soil & Concrete

DIMENSIONS = INCHES

CAT. NO.	FIG	PIPE RANGE	GROUND ROD RANGE	REBAR RANGE	WIRE RANGE		DIMENSIONS			BOX QTY
					MIN	MAX	LENGTH	HEIGHT	WIDTH	
91653	1	1/2-1	3/8-1	3/8-1	10 SOL	2 STR	2.24	1.46	.75	25
91656	2	1/2-1	3/8-1	3/8-1	10 SOL	2 STR	2.24	1.46	.75	25
91652	3	1/2-1	1/2-1	3/8-1	10 SOL	2 STR	2.21	1.15	.63	25

Copper Ground Pipe Clamps - Heavy Duty - Lay-In



- For Connecting Grounding Conductors to Water Pipe, Conduit, Copper Tubing, Ground Rods or Rebar up to 1" in diameter
- Accepts Up To 4/0 Ground Conductor
- Lay-In or Feed Through Configurations
- Cast of High Strength High Conductivity Copper
- Stainless Steel Set Screws
- UL 467 Listed for Direct Burial in Soil & Concrete



FIG 1



FIG 2

DIMENSIONS = INCHES

CAT. NO.	FIG	PIPE RANGE	GROUND ROD RANGE	REBAR RANGE	WIRE RANGE		DIMENSIONS		BOX QTY
					MIN	MAX	LENGTH	HEIGHT	
					SIDE LAY-IN				
91654	I	1/2" -1"	-	-	8 STR	4/0 STR	2.55	2.10	10
91655	I	1-1/4 " - 2"	-	-	8 STR	4/0 STR	3.32	3.20	5
91657	I	2-1/4" - 4"	-	-	8 STR	4/0 STR	5.70	3.75	5
FEED THROUGH									
91610	2	1/2"-1"	3/8 "11"	3/8 "-1"	8 STR	4/0 STR	2.36	1.76	25