


Male Disconnects - 25 Pack



- Vinyl Insulated
- Electro Tin Plated Brass
- Expanded Insulation
- Serrated Barrel
- 167°F (75°C) 300 Volts Max




DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	TAB SIZE	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
01212	RED	22-16	.020 X .187	.189	.256	.748	.394	.067	.157	.020	25	100
01214	RED	22-16	.032 X .250	.250	.303	.827	.394	.067	.157	.016	25	100
01222	BLUE	16-14	.020 X .187	.189	.256	.748	.394	.091	.177	.020	25	100
01224	BLUE	16-14	.032 X .250	.250	.303	.827	.394	.091	.177	.016	25	100
01232	YELLOW	12-10	.032 X .250	.250	.303	.945	.512	.134	.217	.016	25	100

Female Disconnects - 25 Pack



- Vinyl Insulated
- Electro Tin Plated Brass
- Expanded Insulation
- Serrated Barrel
- 167°F (75°C) 300 Volts Max




DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	TAB SIZE	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
01312	RED	22-16	.020 X .187	.197	.252	.748	.394	.067	.157	.014	25	100
01314	RED	22-16	.032 X .250	.260	.295	.807	.394	.067	.157	.014	25	100
01322	BLUE	16-14	.020 X .187	.197	.252	.748	.394	.091	.177	.014	25	100
01324	BLUE	16-14	.032 X .250	.260	.295	.807	.394	.091	.177	.016	25	100
01332	YELLOW	12-10	.032 X .250	.260	.295	.925	.512	.134	.217	.016	25	100

Nylon Fully Insulated Disconnects - 25 Pack



- Nylon Insulated
- Electro Tin Plated Brass
- Expanded Insulation
- Serrated Barrel
- 221°F (105°C) 300 Volts Max
- Rectangular Housing Shape



DIMENSIONS = INCHES

CAT. NO.	TYPE	COLOR	WIRE SIZE AWG	TAB SIZE	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
01411	FEMALE	RED	22-16	.032 X .250	.260	.295	.866	.433	.067	.157	.016	25	100
01412	FEMALE	BLUE	16-14	.032 X .250	.260	.295	.866	.433	.091	.177	.016	25	100
01414	FEMALE	YELLOW	12-10	.032 X .250	.260	.295	.945	.512	.134	.248	.016	25	100
01415	MALE	RED	22-16	.032 X .250	.250	.303	.906	.433	.067	.157	.016	25	100
01416	MALE	BLUE	16-14	.032 X .250	.250	.303	.945	.433	.091	.177	.016	25	100
01418	MALE	YELLOW	12-10	.032 X .250	.250	.303	.984	.512	.134	.248	.016	25	100