




Vinyl Insulated Locking Spade Terminals

**MAXIMUM ELECTRIC CURRENT:**


AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts**INSULATION MATERIAL:** Vinyl**TERMINAL MATERIAL:** Electro-Tin Plated Copper**FEATURES:** Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
11702	RED	22-16	#6	.146	.252	.256	.874	.874	.134	.067	.030	100	1,000
11704	RED	22-16	#8	.169	.319	.256	.874	.874	.134	.067	.030	100	1,000
11706	RED	22-16	#10	.209	.319	.256	.874	.874	.134	.067	.030	100	1,000
11708	BLUE	16-14	#6	.146	.236	.256	.886	.453	.161	.091	.031	100	1,000
11710	BLUE	16-14	#8	.169	.319	.256	.886	.453	.161	.091	.031	100	1,000
11712	BLUE	16-14	#10	.209	.366	.256	.886	.453	.161	.091	.031	100	1,000
11714	YELLOW	12-10	#6	.146	.327	.276	1.035	.555	.248	.134	.039	100	1,000
11716	YELLOW	12-10	#8	.169	.327	.276	1.035	.555	.248	.134	.039	100	1,000
11718	YELLOW	12-10	#10	.209	.354	.276	1.035	.555	.248	.134	.039	100	1,000
11720	YELLOW	12-10	1/4	.252	.472	.472	1.283	.555	.248	.134	.039	100	1,000

Nylon Insulated Locking Spade Terminals

**MAXIMUM ELECTRIC CURRENT:**

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts**INSULATION MATERIAL:** Nylon**TERMINAL MATERIAL:** Electro-Tin Plated Copper - Brazed Seam**FEATURES:** Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BAG QTY
11722	RED	22-16	#6	.146	.252	.256	.866	.433	.134	.067	.030	100	1,000
11724	RED	22-16	#8	.169	.319	.256	.866	.433	.134	.067	.030	100	1,000
11726	RED	22-16	#10	.209	.319	.256	.866	.433	.134	.067	.030	100	1,000
11728	BLUE	16-14	#6	.146	.236	.256	.866	.433	.161	.091	.031	100	1,000
11730	BLUE	16-14	#8	.169	.319	.256	.866	.433	.161	.091	.031	100	1,000
11732	BLUE	16-14	#10	.209	.366	.256	.866	.433	.161	.091	.031	100	1,000
11734	YELLOW	12-10	#6	.146	.327	.276	.992	.512	.252	.134	.039	100	1,000
11736	YELLOW	12-10	#8	.169	.327	.276	.992	.512	.252	.134	.039	100	1,000
11738	YELLOW	12-10	#10	.209	.354	.276	.992	.512	.252	.134	.039	100	1,000
11740	YELLOW	12-10	1/4	.252	.472	.472	1.240	.512	.252	.134	.039	100	1,000