

Vinyl Insulated Female Disconnects

NEW
BULK PACKS



MAXIMUM ELECTRIC CURRENT:


AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 167°F (75°C) 300 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I0308	RED	22-16	.020 X.110	.126	.256	.732	.394	.067	.157	.012	100	1,000
I0310	RED	22-16	.032 X.110	.126	.256	.732	.394	.067	.157	.012	100	1,000
I0312	RED	22-16	.020 X.187	.197	.252	.748	.394	.067	.157	.014	100	1,000
I0311	RED	22-16	.032 X.187	.197	.252	.748	.394	.067	.157	.014	100	1,000
I0313	RED	22-16	.020 X.205	.224	.260	.728	.394	.067	.157	.014	100	1,000
I0314	RED	22-16	.032 X.250	.260	.287	.807	.394	.067	.157	.016	100	1,000
I0314B	RED	22-16	.032 X.250	.260	.287	.807	.394	.067	.157	.016	1,000	10,000
I0316	BLUE	16-14	.020 X.110	.126	.256	.732	.394	.091	.177	.012	100	1,000
I0318	BLUE	16-14	.032 X.110	.126	.256	.732	.394	.091	.177	.012	100	1,000
I0322	BLUE	16-14	.020 X.187	.197	.252	.748	.394	.091	.177	.014	100	1,000
I0323	BLUE	16-14	.032 X.187	.197	.252	.748	.394	.091	.177	.014	100	1,000
I0325	BLUE	16-14	.020 X.205	.224	.260	.728	.394	.091	.177	.014	100	1,000
I0324	BLUE	16-14	.032 X.250	.260	.287	.807	.394	.091	.177	.016	100	1,000
I0324B	BLUE	16-14	.032 X.250	.260	.287	.807	.394	.091	.177	.016	1,000	10,000
I0328	YELLOW	12-10	.020 X.110	.126	.256	.866	.512	.134	.217	.014	100	1,000
I0329	YELLOW	12-10	.032 X.110	.126	.256	.866	.512	.134	.217	.014	100	1,000
I0330	YELLOW	12-10	.020 X.187	.197	.256	.866	.512	.134	.217	.014	100	1,000
I0331	YELLOW	12-10	.032 X.187	.197	.256	.866	.512	.134	.217	.014	100	1,000
I0332	YELLOW	12-10	.032 X.250	.260	.287	.925	.512	.134	.217	.016	100	1,000
I0332B	YELLOW	12-10	.032 X.250	.260	.287	.925	.512	.134	.217	.016	500	10,000

Vinyl Insulated Male Disconnects



MAXIMUM ELECTRIC CURRENT:


AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 167°F (75°C) 300 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I0208	RED	22-16	.020 X.110	.110	.256	.728	.394	.067	.157	.020	100	1,000
I0210	RED	22-16	.032 X.110	.110	.256	.728	.394	.067	.157	.016	100	1,000
I0212	RED	22-16	.020 X.187	.189	.256	.748	.394	.067	.157	.020	100	1,000
I0213	RED	22-16	.032 X.187	.189	.264	.748	.394	.067	.157	.016	100	1,000
I0214	RED	22-16	.032 X.250	.250	.303	.827	.394	.067	.157	.016	100	1,000
I0222	BLUE	16-14	.020 X.187	.189	.256	.748	.394	.091	.177	.020	100	1,000
I0223	BLUE	16-14	.032 X.187	.189	.264	.748	.394	.091	.177	.016	100	1,000
I0224	BLUE	16-14	.032 X.250	.250	.303	.827	.394	.091	.177	.016	100	1,000
I0232	YELLOW	12-10	.032 X.250	.250	.303	.945	.512	.134	.217	.016	100	1,000