

Nylon Fully Insulated Disconnects - Male & Female

NEW
BULK PACKS

UL US
LISTED

MAXIMUM ELECTRIC CURRENT:


AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F (105°C) 300 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation, Rectangular Housing Shape



DIMENSIONS = INCHES

CAT NO.	TYPE	COLOR	WIRE SIZE	TAB SIZE	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I0411	FEMALE	RED	22-16	.250 X .032	.260	.295	.866	.433	.067	.157	.032	100	1,000
I0411B	FEMALE	RED	22-16	.250 X .032	.260	.295	.866	.433	.067	.157	.032	1,000	10,000
I0412	FEMALE	BLUE	16-14	.250 X .032	.260	.295	.866	.433	.091	.177	.032	100	1,000
I0412B	FEMALE	BLUE	16-14	.250 X .032	.260	.295	.866	.433	.091	.177	.032	1,000	10,000
I0414	FEMALE	YELLOW	12-10	.250 X .032	.260	.295	.945	.512	.134	.248	.032	100	1,000
I0414B	FEMALE	YELLOW	12-10	.250 X .032	.260	.295	.945	.512	.134	.248	.032	500	5,000
I0415	MALE	RED	22-16	.250 X .032	.250	.303	.906	.433	.067	.157	.032	100	1,000
I0415B	MALE	RED	22-16	.250 X .032	.250	.303	.906	.433	.067	.157	.032	500	5,000
I0416	MALE	BLUE	16-14	.250 X .032	.250	.303	.945	.433	.091	.177	.032	100	1,000
I0416B	MALE	BLUE	16-14	.250 X .032	.250	.303	.945	.433	.091	.177	.032	500	5,000
I0418	MALE	YELLOW	12-10	.250 X .032	.250	.303	.984	.512	.134	.248	.032	100	1,000

Nylon Fully Insulated Double Crimp Female Disconnects

NEW
BULK PACKS

UL US
LISTED

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24


MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation, Oval Housing Shape



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	FIG.	BAG QTY	MASTER BAG QTY
I1962	RED	22-16	.020 X .110	.126	.256	.768	.433	.067	.157	.012	1	100	1,000
I1964	RED	22-16	.032 X .110	.126	.256	.768	.433	.067	.157	.012	1	100	1,000
I1966	RED	22-16	.020 X .187	.197	.252	.795	.433	.067	.157	.014	2	100	1,000
I1968	RED	22-16	.032 X .187	.197	.252	.795	.433	.067	.157	.014	2	100	1,000
I1970	RED	22-16	.032 X .250	.260	.295	.846	.433	.067	.157	.016	1	100	1,000
I1970B	RED	22-16	.032 X .250	.260	.295	.846	.433	.067	.157	.016	1	1,000	10,000
I1972	BLUE	16-14	.020 X .187	.197	.252	.795	.433	.091	.197	.014	2	100	1,000
I1974	BLUE	16-14	.032 X .187	.197	.252	.795	.433	.091	.197	.014	2	100	1,000
I1976	BLUE	16-14	.032 X .250	.260	.295	.846	.433	.091	.197	.016	1	100	1,000
I1976B	BLUE	16-14	.032 X .250	.260	.295	.846	.433	.091	.197	.016	1	1,000	10,000
I1978	YELLOW	12-10	.032 X .250	.260	.295	.953	.512	.134	.256	.016	2	100	1,000

Nylon Fully Insulated Double Crimp Male Disconnects

UL US
LISTED

MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24


MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation, Oval Housing Shape



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I1980	RED	22-16	.020 X .187	.250	.256	.866	.433	.067	.157	.016	100	1,000
I1981	RED	22-16	.032 X .187	.250	.256	.866	.433	.067	.157	.016	100	1,000
I1982	RED	22-16	.032 X .250	.250	.303	.945	.433	.067	.157	.016	100	1,000
I1983	BLUE	16-14	.020 X .187	.250	.256	.866	.433	.091	.197	.016	100	1,000
I1985	BLUE	16-14	.032 X .187	.250	.256	.866	.433	.091	.197	.016	100	1,000
I1984	BLUE	16-14	.032 X .250	.250	.303	.945	.433	.091	.197	.016	100	1,000
I1986	YELLOW	12-10	.032 X .250	.250	.303	1.024	.512	.134	.256	.016	100	1,000

