




Vinyl Insulated Piggy Back Disconnects



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 167°F (75°C) 300 Volts

INSULATION MATERIAL: Vinyl


TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	WI	F	FI	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2012	RED	22-16	.032 X.250	.260	.250	.315	.323	.866	.394	.067	.157	.016	100	1,000
I2014	BLUE	16-14	.032 X.250	.260	.250	.315	.323	.866	.394	.091	.177	.016	100	1,000
I2016	YELLOW	12-10	.032 X.250	.260	.250	.315	.323	.945	.512	.134	.217	.016	100	1,000

Nylon Insulated Double Crimp Piggy Back Disconnects



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass


DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	WI	F	FI	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2022	RED	22-16	.032 X.250	.260	.250	.315	.323	.906	.433	.067	.157	.016	100	1,000
I2024	BLUE	16-14	.032 X.250	.260	.250	.315	.323	.906	.433	.091	.197	.016	100	1,000
I2026	YELLOW	12-10	.032 X.250	.260	.250	.315	.323	.945	.512	.134	.256	.016	100	1,000

Nylon Fully Insulated Double Crimp Piggy Back Disconnects



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	NEMA TAB	W	WI	F	FI	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2032	RED	22-16	.032 X.250	.260	.250	.315	.323	.846	.433	.067	.157	.016	100	1,000
I2034	BLUE	16-14	.032 X.250	.260	.250	.315	.323	.846	.433	.091	.197	.016	100	1,000