

Vinyl Insulated Receptacle Disconnects



MAXIMUM ELECTRIC CURRENT:



AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO..	COLOR	WIRE SIZE AWG	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2072	RED	22-16	.154	.276	.846	.394	.067	.157	.016	100	1,000
I2074	BLUE	16-14	.154	.276	.846	.394	.091	.177	.016	100	1,000
I2076	BLUE	16-14	.193	.276	.846	.394	.091	.177	.016	100	1,000
I2078	YELLOW	12-10	.193	.276	.965	.512	.134	.217	.018	100	1,000

Nylon Insulated Double Crimp Receptacle Disconnects



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24


MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO..	COLOR	WIRE SIZE AWG	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2082	RED	22-16	.154	.276	.886	.433	.067	.157	.016	100	1,000
I2084	BLUE	16-14	.154	.276	.886	.433	.091	.197	.016	100	1,000
I2086	BLUE	16-14	.193	.276	.886	.433	.091	.197	.016	100	1,000
I2088	YELLOW	12-10	.193	.276	.965	.512	.134	.256	.018	100	1,000

Nylon Fully Insulated Double Crimp Receptacle Disconnects



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	3	4	7	10	15	20	24



MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation



DIMENSIONS = INCHES

CAT. NO..	COLOR	WIRE SIZE AWG	W	F	L	B	C	D	T	BAG QTY	MASTER BAG QTY
I2092	RED	22-16	.154	.276	.992	.433	.067	.157	.016	100	1,000
I2094	BLUE	16-14	.154	.276	.992	.433	.091	.197	.016	100	1,000
I2096	BLUE	16-14	.193	.276	1.063	.433	.091	.197	.016	100	1,000