

Vinyl Insulated Reducing Butt Splice Connector




MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 167°F (75°C) 600 Volts

INSULATION MATERIAL: Vinyl

TERMINAL MATERIAL: Electro-Tin Plated Copper Brazed Seam



DIMENSIONS = INCHES

CAT. NO.	WIRE RANGE AWG	COLOR CODE	L	D	D1	D2	BAG QTY	MASTER BAG QTY
I2135	16-14 TO 22-18	BLUE WITH RED RING	.965	.177	.067	.091	100	1,000
I2136	12-10 TO 22-18	YELLOW WITH RED RING	1.22	.248	.067	.134	100	1,000
I2137	12-10 TO 16-14	YELLOW WITH BLUE RING	1.22	.248	.091	.134	100	1,000
I2138	8 TO 16-14	RED WITH BLUE RING	1.406	.335	.091	.177	100	1,000
I2139	8 TO 12-10	RED WITH YELLOW RING	1.406	.335	.134	.177	100	-
I2140	6 TO #8	BLUE WITH RED RING	1.172	.413	.177	.232	100	-

Nylon Insulated Butt Splice Connectors

NEW
BULK PACKS



MAXIMUM ELECTRIC CURRENT:

AWG	26	24	22	20	18	16	14	12	10
AMP	5.5	7	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

CONNECTOR MATERIAL: Copper

INSULATION MATERIAL: Nylon

FEATURES: Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	L	D	D1	MATERIAL	BAG QTY	MASTER BAG QTY
I2142	YELLOW	26-22	.787	.079	.051	TUBULAR COPPER	100	1,000
I2142B	YELLOW	26-22	.787	.079	.051	TUBULAR COPPER	1,000	20,000
I2144	RED	22-16	1.075	.126	.067	COPPER PLATE	100	1,000
I2144B	RED	22-16	1.075	.126	.067	COPPER PLATE	1,000	10,000
I2146	BLUE	16-14	1.075	.150	.091	COPPER PLATE	100	1,000
I2146B	BLUE	16-14	1.075	.150	.091	COPPER PLATE	1,000	10,000
I2148	YELLOW	12-10	1.075	.209	.134	COPPER PLATE	100	1,000
I2148B	YELLOW	12-10	1.075	.209	.134	COPPER PLATE	500	5,000
I2149	RED	8	1.457	.272	.181	COPPER PLATE	100	-

Nylon Insulated Butt Splice Connector Flared Entry



MAXIMUM ELECTRIC CURRENT:


AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 221°F (105°C) 600 Volts

CONNECTOR MATERIAL: Copper

INSULATION MATERIAL: Nylon

FEATURES: Expanded Insulation



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	L	D	D1	BAG QTY	MASTER BAG QTY
I2192	RED	22-16	.992	.157	.067	100	1,000
I2193	BLUE	16-14	.992	.177	.091	100	1,000
I2194	YELLOW	12-10	1.11	.248	.134	100	1,000