

Heat Shrinkable - Ring Terminals



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 600 Volts


SHRINK TEMP: 302°F (150°C)

RESISTANT TEMP: 14°F ~ 221°F (-10°C ~ 105°C)

INSULATION MATERIAL: High Density PE Heat Shrink

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Brazed Seam, Serrated Barrel



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	D2	W	L	BAG QTY	MASTER BAG QTY
I2212	RED	22-16	#6	.217	.984	100	1,000
I2214	RED	22-16	#8	.315	1.122	100	1,000
I2216	RED	22-16	#10	.315	1.122	100	1,000
I2218	RED	22-16	1/4	.457	1.358	100	1,000
I2220	RED	22-16	5/16	.457	1.358	100	1,000
I2222	RED	22-16	3/8	.535	1.476	100	1,000
I2224	BLUE	16-14	#6	.260	1.043	100	1,000
I2226	BLUE	16-14	#8	.335	1.201	100	1,000
I2228	BLUE	16-14	#10	.374	1.201	100	1,000
I2230	BLUE	16-14	1/4	.472	1.398	100	1,000
I2232	BLUE	16-14	5/16	.472	1.398	100	1,000
I2234	BLUE	16-14	3/8	.535	1.476	100	1,000
I2236	YELLOW	12-10	#8	.374	1.339	100	1,000
I2238	YELLOW	12-10	#10	.472	1.476	100	1,000
I2240	YELLOW	12-10	1/4	.591	1.654	100	1,000
I2242	YELLOW	12-10	5/16	.591	1.654	100	1,000
I2244	YELLOW	12-10	3/8	.756	1.831	100	1,000
I2246	YELLOW	12-10	1/2	.756	1.831	100	1,000
I2250	RED	8	5/16	.591	1.693	100	-
I2251	RED	8	3/8	.591	1.693	100	-

Heat Shrinkable - Spade Terminals



MAXIMUM ELECTRIC CURRENT:

AWG	22	20	18	16	14	12	10
AMP	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 600 Volts



SHRINK TEMP: 302°F (150°C)

RESISTANT TEMP: 14°F ~ 221°F (-10°C ~ 105°C)

INSULATION MATERIAL: High Density PE Heat Shrink

TERMINAL MATERIAL: Electro-Tin Plated Copper

FEATURES: Serrated Barrel, Brazed Seam



DIMENSIONS = INCHES

CAT. NO.	COLOR	WIRE SIZE AWG	D2	W	L	BAG QTY	MASTER BAG QTY
I2252	RED	22-16	#6	.252	1.154	100	1,000
I2254	RED	22-16	#8	.283	1.165	100	1,000
I2256	RED	22-16	#10	.374	1.181	100	1,000
I2257	BLUE	16-14	#4	.224	1.122	100	1,000
I2258	BLUE	16-14	#6	.236	1.122	100	1,000
I2260	BLUE	16-14	#8	.283	1.161	100	1,000
I2262	BLUE	16-14	#10	.366	1.201	100	1,000
I2264	YELLOW	12-10	#8	.354	1.319	100	1,000
I2266	YELLOW	12-10	#10	.354	1.319	100	1,000
I2268	YELLOW	12-10	1/4	.472	1.614	100	1,000