


High Temperature Ring Terminals

NEW
BULK PACKS

- Nickel Plated Steel
- Butted Seam
- Max Temp: 900°F (482°C)
- Applications Include: Electric Space Heaters, HVAC Controls, Industrial Automation, Commercial Ovens and Fryers, Industrial kilns




DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BOX QTY
12512	22-16	6	.146	.260	.248	.567	.189	.134	.067	.030	100	1,000
12512B	22-16	6	.146	.260	.248	.567	.189	.134	.067	.030	1,000	20,000
12514	22-16	10	.209	.315	.276	.622	.189	.134	.067	.030	100	1,000
12514B	22-16	10	.209	.315	.276	.622	.189	.134	.067	.030	1,000	20,000
12515	22-16	1/4	.252	.457	.433	.858	.189	.134	.067	.030	1,000	10,000
12516	16-14	6	.146	.260	.248	.567	.189	.161	.091	.031	100	1,000
12516B	16-14	6	.146	.260	.189	.504	.189	.161	.091	.031	1,000	20,000
12518	16-14	10	.209	.335	.291	.650	.189	.161	.091	.031	100	1,000
12518B	16-14	10	.209	.335	.291	.650	.189	.161	.091	.031	1,000	20,000
12520	16-14	1/4	.252	.472	.433	.858	.189	.161	.091	.031	100	1,000
12521	12-10	6	.146	.283	.240	.618	.236	.220	.134	.039	100	1,000
12522	12-10	10	.209	.374	.327	.748	.236	.220	.134	.039	100	1,000
12522B	12-10	10	.209	.374	.327	.748	.236	.220	.134	.039	1,000	10,000
12523	12-10	1/4	.252	.472	.413	.886	.236	.220	.134	.039	100	1,000
12523B	12-10	1/4	.252	.472	.413	.886	.236	.220	.134	.039	1,000	10,000
12525	12-10	5/16	.331	.591	.524	1.063	.236	.220	.134	.039	100	1,000
12526	12-10	3/8	.413	.591	.524	1.063	.236	.220	.134	.039	100	1,000
12524	8	1/4	.252	.472	.366	.937	.335	.283	.177	.047	100	-

High Temperature Fork/Spade Terminals

- Nickel Plated Steel
- Butted Seam
- Max Temp: 900°F (482°C)
- Applications Include: Electric Space Heaters, HVAC Controls, Industrial Automation, Commercial Ovens and Fryers, Industrial kilns




DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	STUD SIZE	D2	W	F	L	E	D	DI	T	BAG QTY	MASTER BOX QTY
12530	22-16	10	.209	.319	.256	.63	.189	.134	.067	.030	100	1,000
12532	16-14	10	.209	.319	.256	.63	.189	.161	.091	.031	100	1,000
12534	12-10	10	.209	.354	.276	.72	.236	.22	.134	.039	100	1,000

High Temperature Disconnects

- Nickel Plated Steel
- Butted Seam
- Max Temp: 900°F (482°C)
- Applications Include: Electric space heaters, HVAC Controls, Industrial Automation, Commercial Ovens and Fryers, Industrial kilns



DIMENSIONS = INCHES

CAT. NO.	WIRE SIZE AWG	TAB SIZE	TYPE	W	F	L	E	D	DI	WALL THICKNESS	BAG QTY	MASTER BOX QTY
12541	22-16	.187 X .020	FEMALE	.199	.248	.543	.189	.106	.067	.012	10	1,000
12542	16-14	.187 X .020	FEMALE	.199	.248	.543	.189	.130	.091	.014	100	1,000
12544	16-14	.250 X .032	FEMALE	.260	.295	.598	.189	.130	.091	.016	100	1,000
12546	16-14	.250 X .032	MALE	.260	.307	.740	.252	.130	.091	.031	100	1,000
12547	12-10	.250 X .032	FEMALE	.260	.295	.642	.252	.177	.134	.035	100	1,000

