


Plastic Cable Clamps

- Secure cable, tubing, wires, fiber optics, etc.
- Used for construction, maintenance & assembly line operations
- Use in control cabinets, panels and general applications
- Molded in the open position for easy assembly
- Tough, durable, yet extremely lightweight
- Operating Temperature Range:
-40°F to 185°F (-40°C to 85°C)
- Clean, smooth edges prevent abrasion & facilitate easy handling
- Use with #10 screw (.18") (not included)
- Made from UL approved Nylon 6/6, 94V-2

DIMENSIONS = INCHES

CAT. NO.	(CLOSED) B	C	WIDTH D	SCREW HOLE	BAG QTY
NATURAL COLOR					
22412	1/8"	.37	.38	.18	10
22414	3/16"	.41	.38	.18	10
22416	1/4"	.39	.39	.18	10
22418	3/8"	.49	.47	.18	10
22420	1/2"	.60	.47	.18	10
22422	5/8"	.72	.47	.18	10
22424	3/4"	.72	.47	.18	10
22426	1"	.87	.47	.18	10
22428	1 1/4"	1.03	.47	.18	10
22430	1 1/2"	1.18	.47	.18	10
ULTRAVIOLET BLACK					
22442	1/8"	.37	.38	.18	10
22444	3/16"	.41	.38	.18	10
22446	1/4"	.39	.39	.18	10
22448	3/8"	.49	.47	.18	10
22450	1/2"	.60	.47	.18	10
22452	5/8"	.72	.47	.18	10
22454	3/4"	.72	.47	.18	10
22456	1"	.87	.47	.18	10
22458	1 1/4"	1.03	.47	.18	10
22460	1 1/2"	1.18	.47	.18	10



WIRE MANAGEMENT
Cable Clamps