## Lockout Hasps

- Accepts padlocks up to 3/8" shackle diameter
- Manufactured from 12 gauge steel
- .060 malleable steel plate for maximum security
- Red plastic coating for visibility
- Multiple party lockouts with same device
- Solid Steel U Jaws
- Protection for electric, gas, water, steam, acid & pneumatic control units & levers
- Prevents engagement of circuit breaker boxes & disconnect switches
- Allows up to 6 workers to lock out a single energy source
- Superior resistance to rust and added dielectric strength

		DIMENSIONS = INCHES
CAT. NO.	SIZE	BOX QTY
21694	["	10
21696	I-I/2"	10

## Padlocks

- Solid Anodized Aluminum
- Lock Body measures 1-1/2" wide x 3/4" thick x 1-13/16" high
- Chrome plated hardened steel shackle is 1/4" wide x 1" vertical clearance x 25/32" horizontal clearance
- Double Ball Bearing Locking Mechanism
- Re-keyable 5 pin brass cylinder & anti-pick pinning
- Each lock comes with 2 keys
- Complies with OSHA Rule (1910.147) for Safety Lockout Guards Against Accidental Start-Up Injuries
- Keyed Alike Locks that are the Same Color Use The Same Key

CAT. NO.	COLOR	BOX QTY	
KEYED DIFFERENTLY			
21632	BLUE	5	
21634	BLACK	5	
21640	GREEN	5	
21642	GOLD	5	
KEYED ALIKE (EACH COLOR IS KEYED THE SAME)			
21656	BROWN	5	
21660	GREEN	5	
21662	GOLD	5	

## Lockout Tags

- Lockout tags warn of Hazard in and around Machinery, Equipment, Valves, etc.
- Made of rigid 15 mil vinyl with 7/16" brass grommet
- Easy to write on with permanent marker
- Moisture and mildew resistant for outdoor use
- Each durable long lasting tag is 5-3/4" x 3"
- Available in standard packs of 5 tags

CAT. NO.	LEGEND	TAGS PER PACK
21512	DO NOT OPERATE	5
21524	DO NOT ENERGIZE	5
21528	EQUIPMENT LOCKED OUT (WITH STRIPES)	5

WWW.MORRISPRODUCTS.COM







D66

1-888-777-6678