


## Beam Clamps





- Fast installation; fits beam flange up to 1/2"
- Used with 1/4" and 3/8" threaded rod, "S" hooks, conduit hangers, electrical box, & #10-24 or 1/4"-20 bridle rings
- Tapping 1/4"-20 bottom and back.
- Also #10-24 tapping on back

**Static Load Limit: 100 lbs**

DIMENSIONS = INCHES

CAT. NO.	ACCOMMODATES		BOX QTY
	FLANGE	DROP ROD	
18016	UP TO 1/2" THICK	1/4-3/8	100

## Spring Steel Beam Clamps



- Can be used to suspend boxes, fixtures and bridle rings to beam flanges 1/8" to 1/2"
- Bottom & Back Tapped 1/4-20

**Static Load Limit: 75 lbs to 100 lbs**  
**Front Thread 75 lbs**  
**Rear Thread 100 lbs**



(static load limits cannot be combined)

DIMENSIONS = INCHES

CAT. NO.	FLANGE THICKNESS	BOX QTY
18012	1/8-1/4	100
18014	5/16-1/2	100



## Spring Steel Beam Clamps - 1/4-20 X 3/8" Stud



- Can be used to suspend boxes, fixtures and bridle rings to beam flanges 1/8" to 3/4"
- Beam clamp with 1/4"-20 x 3/8" staked stud used to suspend box from bottom of beam


**Static Load Limit: 75 lbs**

DIMENSIONS = INCHES

CAT. NO.	FLANGE THICKNESS	BOX QTY
18123	1/8-1/4	100
18124	5/16-1/2	100



## Spring Steel Beam Clamps Universal



- Can be used on Bulb Tees & Beams
- Clearance for 1/4" Bolt in Tab

**Static Load Limit: 200 lbs**

DIMENSIONS = INCHES

CAT. NO.	FLANGE THICKNESS	BOX QTY
18018	1/8 TO 1/4	100
18020	5/16 TO 1/2	100
18152	9/16 TO 3/4	100

