

## Regular Bodied 303 Series Clear Cements



- Regular Bodied Clear Cement for PVC pipe and fittings up to 4" diameter for Sch. 40 pipe & up to 2" for Sch. 80 with interference fit
- Recommended application temperature 40°F to 110°F
- Sets up Quickly
- Low-Voc Compliant, Meets ASTM-D2564

CAT. NO.	SIZE	WEIGHT PER CASE (LBS)	CASE QTY
G30366S	4 OZ	9	24
G30356S	8 OZ	16	24
G30346S	16 OZ	27	24
G30336S	32 OZ		12
G30324	128 OZ		6

## Medium Bodied Clear Cements



- Medium Bodied Clear Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80
- Recommended application temperature 40°F to 110°F
- Low-Voc Compliant, Meets ASTM-D2564

CAT. NO.	OLD CAT. NO.	SIZE	WEIGHT PER CASE (LBS)	CASE QTY
G31017	G40466S	4 OZ	9	24
G40456S		8 OZ	16	24
G40446S		16 OZ	27	24
G40436S		32 OZ		12
G1224	G40424	128 OZ		6

## Medium Bodied Gray Cements



- Medium Bodied Gray Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80 Conduits
- Recommended application temperature 40°F to 110°F
- Low-Voc Compliant, Meets ASTM-D2564

CAT. NO.	SIZE	WEIGHT PER CASE (LBS)	CASE QTY
G40336S	32 OZ	26	12
G40324	128 OZ	52	6

## Medium Bodied Gray Cement



- Fast setting gray cement solvent welds PVC, dauber included
- Medium viscosity easily fills gaps and provides more working time
- Can be used on all schedules and classes of PVC pipe and fittings up to 6" dia.
- Low-VOC Compliant
- Meets ASTM Standard D2564 and complies with NSF/ANSI 61

CAT. NO.	SIZE	WEIGHT PER CASE (LBS)	CASE QTY
G30885	32 OZ	28	24