Portable Hand Torch



- Self igniting hand torch eliminates the need for a flint lighter.
- Lightweight and portable.
- Can be operated with Propane or MAP-Pro™ (Propylene).
- Features trigger lock with instant safety release.
- Full size comfort grip.
- 360° swivel tip.
- Operates in any position, even upside down.
- Includes swirl combustion tip end.

CAT. No.	DESCRIPTION	ИОМ	ORDER Multiple
T525-TORCH	PORTABLE HAND TORCH	EA	1

FireStop Caulk

- Odorless
- Water Based, Paintable
- Easy Gunability
- 1 year Shelf Life
- Red Color
- **UL Classified**
- Zero VOC's
- Unaffected by Freeze/Thaw
- Adhesion to almost Any Surface
- Non-Corrosive & Non-Combustible
- Non-Toxic Environmentally Safe
- Non-Combustible Firestopping Caulk
- UL Classified for 1 & 2 Hour Fire Rated Walls & Floors
- Forms a Barrier to Prevent the Spread of Flames, Smoke & Toxic Fumes
- One Part Non-Intumescent Silicate based Firestop Sealant
- Tested & Approved for Use as Filler for Through Penetration Firestop Systems
- Meets Fire/Draft/Smoke criteria for BOCA - CABO - UPC - SBCC/IRC
- Suitable for Commercial, Industrial & Residential Firestop Requirements
- ASTM E-84 O Flame & O Smoke Certified
- ASTM E-136 Residential Use Certified
- ASTM E-814 Commercial Use Compatible





DESCRIPTION	COVERAGE 1/2" X 1/4" Bead	CASE QTY
10.5 OZ. TUBE	16'	12
290Z. TUBE	45'	12
I GALLON PAIL	180'	1
5 GALLON PAIL	896'	Ī
	10.5 OZ. TUBE 290Z. TUBE 1 GALLON PAIL	10.5 OZ. TUBE 16' 290Z. TUBE 45' 1 GALLON PAIL 180'

Map-Pro and Propane Gas



 Map-Pro and Propane Gas are tanks that can be used to weld products.

T525-MTI

T525-PTI

CAT. No.	DESCRIPTION	ИОМ	ORDER MULTIPLE
T525-MTI	MAP-PRO GAS – 14 OZ.	EA	12
T525-PTI	PROPANE GAS – 14.1 OZ.	EA	12

Multi Color Test Leads



- Easy to use multi-colored test leads.
- 5 colors (white, red, black, yellow, green).
- 2 connections each for easy testing on the job.
- Wire is 18 gauge.
- 18" long.

GAT. NO.	DESCRIPTION		ORDER Multiple
TCT800	MULTI COLOR TEST LEADS	EA	1

Silicone Sealant



- Seals electrical components & provides weather-tight closure for electrical boxes & exterior fixtures
- Acetic cure anti-fungus Acetoxy based silicone sealant suitable for construction & household repairs
- Exhibits an excellent sealing and adhesion to metal, glass, tiles, ceramics, fiberglass, aluminum, non-oily wood, painted surfaces, plastic, rubber, fiber & other non-porous materials
- Protects & seals waterproof & flexible indoors & outdoors
- Fills voids & irregularities. Not paintable
- RTV 100% Silicone, flexible from -60°F to 450°F, 20°F min dispensing temp.
- High Temperature Sealant rated from -85°F to 500°F meets Federal Spec. TT-S-001543A
- Meets FDA Reg. #21 CFR 177.2600, Federal Spec. TT-S-00230C, MIL-A-46106A Amend. 2, ASTM C-920
- Complies with EcoSeal Standards, LEED 2009. NAHB Green Guidelines, SCAQMD Rule #1168 OTC, CARB, BAAQMD
- 10.3 OZ Tubes

CAT. NO.	COLOR	CASE QTY	
99912	CLEAR	12	
99916	WHITE	12	
99913	SILVER	12	
99914	BLACK	12	
HI-TEMP SILICONE			
99911	RED	12	