



Decorative Receptacles



- 2 Pole 3 Wire
- Back & Side Wired
- Made of GE Lexan, Steel Mounting Strap
- Washer Type Break Off Plaster Ears
- Large Head Captive Tri-Combination Screws
- Green Hex-Head Ground Screw
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F
- Accepts #12 or #14 Stranded or Solid CU
- (Push-In #14 Solid Only)

AMPS	VOLTAGE	COLOR	RESIDENTIAL GRADE	FIGURE	BOX QTY	CASE QTY
15 AMP 125V 5-15R						
15	125	IVORY	82015	I	10	200
		WHITE	82016	I	10	200
		BROWN	82017	I	10	200
		ALMOND	82018	I	10	200

Industrial Grade Decorative Receptacles



- 2 Pole 3 Wire 5-15R
- Back & Side Wired
- Made of GE Lexan, Steel Mounting Strap
- Washer Type Break Off Plaster Ears
- Large Head Captive Tri-Combination Screws
- Dual Ground Self Ground Clip/Screw
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F
- Accepts #12 or #14 Stranded or Solid CU
- (Push-In #14 Solid Only)

AMPS	VOLTAGE	COLOR	INDUSTRIAL GRADE	BOX QTY	CASE QTY
15 AMP 125V 5-15R					
15	125	IVORY	82210	10	200
		WHITE	82211	10	200
15 AMP 250V 6-15R					
15	250	IVORY	82215	10	200
		WHITE	82216	10	200
20 AMP 125 V 5-20R					
20	125	IVORY	82180	10	200
		WHITE	82181	10	200
20 AMP 250V 6-20R					
20	250	IVORY	82220	10	200
		WHITE	82221	10	200

Isolated Ground Decorative Receptacles



- Protect Sensitive Electronic Equipment and Eliminate Electromagnetic interference by Providing Separate Path to Ground
- Back and Side Wired
- 2 Pole 3 Wire 5-15R
- Unique Screw Terminal Guards
- Provide Fast, Easy Installation
- Isolated Ground
- Washer Type Break Off Plaster Ears
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F

AMPS	VOLTAGE	COLOR	ISOLATED GROUND	BOX QTY	CASE QTY
15 AMP 125V 5-15R					
15	125	IVORY	81910	10	200
		WHITE	81911	10	200
		ORANGE	81914	10	200
15 AMP 250V 6-15R					
15	250	IVORY	81920	10	200
		WHITE	81921	10	200
		ORANGE	81924	10	200
20 AMP 125V 5-20R					
20	125	IVORY	81915	10	200
		WHITE	81916	10	200
		ORANGE	81919	10	200
20 AMP 250V 6-20R					
20	250	IVORY	81925	10	200
		WHITE	81926	10	200
		ORANGE	81929	10	200